

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices: Tyan S2865/Opteron 154

SPECweb99_SSL =1345

Zeus Technology Ltd.: Zeus Web Server V4.2r4

Test Date: Aug-2005
Tester: Advanced Micro Devices

Hardware Avail: Sep-2005 OS Avail: Jul-2005 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Nov-2003 SPEC license #: 49

Hardware

Vendor: Advanced Micro Devices
Model: Tyan S2865/Opteron 154
Processor: AMD Opteron 154, 2.8 GHz
Processors: 1 core, 1 chip, 1 core/chip
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1MB on chip
Other Cache: none
Memory: 4 GB PC3200 DDR
Disk Subsystem: 4 74GB 10KRPM SATA Drives
Disk Controllers: Onboard SATA
Other Hardware: 1 SMC 8624T Gigabit Switch

Software

Operating System: SuSE Linux Enterprise Server 9 SP2 (32 bit)
File System: ext2
Other Software: none

HTTPS Software

Vendor: Zeus Technology Ltd.
HTTPS Software: Zeus Web Server V4.2r4
API: Zeus PEPP 0.9pre1 ISAPI for Dynamic Content
Server Cache: None
Log Mode: Binary Log Format

Test Sponsor

Test Date: Aug-2005
Tested By: Advanced Micro Devices
SPEC License: 49

Network

of Controllers: 1
Network Controllers: Broadcom BCM5712
of Nets: 1
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 6
Model: Sun V20Z
Processor: AMD Opteron 244
of Processors: 2
Memory: 2048MB
Network Controller: Onboard Broadcom BCM5703 Gigabit Ethernet
Operating System: SuSE SLES 8 SP3
Compiler: gcc v3.3.3

Notes/Tuning Information

SUT Notes

- 1 SATA 10K 74GB disk with ext3 for root
- 1 SATA 10K 74GB disk with ext2 for logs
- 2 SATA 10K 74GB disks with in software RAID 0 configuration with ext2 for fileset

Operating System Notes

irqbalancer disabled

Each NIC's TX queue length set to 40000 via ifconfig, default 1000

Log/Fileset filesystem mounted with "noatime,nodiratime,noacl", no inode access time updating, no access control lists
ulimit -n 34949, sets number of open files, default 1024
fs.file-max = 140797, maximum number of open file handles, default 1024

Tuning Parameters:

- net.ipv4.ip_forward = 0
- net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
- net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
- net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
- net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
- net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
- net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
- net.core.wmem_default = 10000000, default send socket buffer size, default 65535
- net.core.optmem_max = 10000000, default 10240
- net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
- net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072

For more
Information
Contact

SPEC

info@spec.org
http://www.spec.org

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

- net.ipv4.tcp_mem = 30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768

HTTPS Software Notes

Zeus Configuration:

tuning!bind_any no

tuning!unique_bind yes

tuning!so_wbuff_size 1048576

tuning!softservers no

tuning!cbuff_size 65536

tuning!clientfirst_optimise yes

tuning!ssl_sessioncache_size 7507

tuning!listen_queue_size 8192

tuning!keepalive yes

tuning!keepalive_timeout 360

tuning!multiple_accept yes

tuning!keepalive_max -1

tuning!maxaccept 2048

tuning!modules!cgi!enabled yes

tuning!isapi!enabled yes

tuning!max_connections 3000

tuning!modules!stats!enabled no

tuning!modules!nsapi!enabled no

Refer to AMD-Zeus-tuning-20050509.txt for a description of Zeus tuning parameters

HTTP API Notes

Zeus PEPP configured with command: ./Configure --ssl=yes

Zeus PEPP compiled with default gcc (v3.3.3)

Client Notes

Client code configured with command: ./configure --enable-posix-threads

Client code compiled with default gcc (v3.2.2)

net.ipv4.ip_local_port_range 1024 65535

Clients use DDR PC2700 memory

Other Notes

Tuning Disclosure: See above

Dynamic API: HP-20020724-API.tgz

Client kernel config: Default SuSE SLES8 x86 SP3 (2.4.21-138-smp)

Server kernel config: Default SLES9 SP1 32 bit 2.6.5-7.139-bigsm

SUT requires a Tyan S2865 motherboard, an eATX 4 hard drive capable case with a minimum 420 watt power supply.