

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard: HP Integrity rx1600  
Zeus Technology Limited: Zeus 4.2r3

SPECweb99\_SSL =1278

Test Date: Nov-2003  
Tester: Hewlett-Packard Company

Hardware Avail: Feb-2004 OS Avail: Sep-2003 HTTPS Software Avail: Jul-2003 Sup. Software Avail: Sep-2003 SPEC license #: 3

## Hardware

Vendor: Hewlett-Packard  
Model: HP Integrity rx1600  
Processor: Low Voltage Intel Itanium 2 1.0 GHz  
# Processors: 2 cores, 2 chips, 1 core/chip  
Primary Cache: 16KBI+16KBD on chip  
Secondary Cache: 256KB unified on chip  
Other Cache: 1536KB unified on chip  
Memory: 8GB (4x2GB)  
Disk Subsystem: 1x36GB, 1x73GB (15K RPM)  
Disk Controllers: Ultra320 Wide LVD SCSI (internal)  
Other Hardware: HP ProCurve Switch 2724

## Software

Operating System: HP-UX 11i v2  
File System: See SUT Notes  
Other Software: B3901BA HP C/ANSI C

## HTTPS Software

Vendor: Zeus Technology Limited  
HTTPS Software: Zeus 4.2r3  
API: ISAPI  
Server Cache: None  
Log Mode: Binary Log Format

## Test Sponsor

Test Date: Nov-2003  
Tested By: Hewlett-Packard Company  
SPEC License: 3

## Network

# of Controllers: 2  
Network Controllers: HP A6825A  
# of Nets: 2  
Type of Nets: Gigabit Ethernet  
Network Speed: 1 Gb/s  
MSL (sec): 30 (Non RFC1122)  
Time-Wait (sec): 60 (Non RFC1122)  
MTU: 1500

## Clients

# of Clients: 6  
Model: HP Integrity rx2600  
Processor: Intel Itanium 2 1.0 GHz  
# of Processors: 2  
Memory: 6GB  
Network Controller: HP A6825A  
Operating System: HP-UX 11i v1.6  
Compiler: B3901BA B.11.22 HP C/ANSI C

## Notes/Tuning Information

### SUT Notes

All file systems are HFS  
1 (36GB) disk used for OS  
1 (73GB) disk split into three logical volumes using LVM  
lv01 (21GB) mounted with behind option used for doc\_root & post.log  
lv02 (24GB) mounted with read-only option used for the file\_set  
lv03 (24GB) mounted with largefiles, behind options used for logs  
File system containing logs is 64KB block size (def. 8KB) and 8KB fragments (def. 1KB)  
Bound each zeus instance to the processor corresponding to its NIC  
Processor binding is performed by: mpsched -c cpu# -p pid  
Set page size attribute for zeus.web and zeus.cgi binaries  
chattr +pd 64K +pi 64K zeus.cgi  
chattr +pd 64M +pi 64M zeus.web

### Operating System Notes

HP-UX Tunable Parameters:  
dbc\_max\_pct=30 Max Buffer Cache Size as Percent of RAM (50)  
dbc\_min\_pct=30 Min Buffer Cache Size as Percent of RAM (5)  
fs\_async=1 Enables write calls to return before write operation is complete Boolean (0)  
maxfiles=3000 Soft File Limit per Process (60)  
maxfiles\_lim=3000 Hard File Limit per Process (1024)  
nfile=6000 Max number of open files (790)  
ninode=60000 Max number of inodes (444)  
scsi\_max\_qdepth=64 Max number of concurrent requests to a SCSI device(8)  
tphashsz=16384 Relative Scaling Factor for TCP & IP Int. Tables(2048)  
vps\_ceiling=4096 Max System selected page size [KB] (16)

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

## Notes/Tuning Information (Continued)

### Operating System Notes (Continued)

vps\_pagesize=64 Default User page size [KB] (4)  
vxfs\_ifree\_timelag=3600000 VxFS Free Inode minimum existence time (0)

### HTTPS Software Notes

Zeus Global Parameters:

```
tuning!cache_files      356750
tuning!cache_max_bytes  0
tuning!cache_small_file 4096
tuning!cache_large_file 999999
tuning!cache_stat_expire 86400
tuning!cache_flush_interval 86400
tuning!listen_queue_size 1024
tuning!multiple_accept  yes
tuning!so_rbuff_size    0
tuning!so_wbuff_size    1048576
tuning!cbuff_size       65536
tuning!keepalive        yes
tuning!keepalive_timeout 1200
tuning!keepalive_max    -1
tuning!timeout          600
tuning!unique_bind      yes
tuning!bind_any         no
tuning!sendfile         no
tuning!ssl_keepalive    yes
tuning!ssl_sessioncache_size 5011
tuning!ssl_sessioncache_expiry 120
tuning!ssl_diskcache    no
tuning!modules!cgi!cbuff_size 1048576
tuning!modules!cgi!cleansize 0
tuning!softservers      no
tuning!use_select        yes
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!modules!isapi!enabled no
tuning!cache_cooling_time 0
tuning!maxaccept        2048
Zeus runningsite configuration:
modules!security!enabled yes
modules!cgi!enabled yes
modules!isapi!enabled yes
```

### HTTP API Notes

Zeus PEPP Toolkit(0.8) used for SPECweb99\_SSL dynamic content  
./Configure --sendfile=no --checkconfig=yes --locking=semop --ssl=yes --64bit=yes  
Compiled with HP C/ANSI C developer's Bundle (B3901BA)  
CFLAGS=+Ofaster +DD64 +DSitanium2  
LDFLAGS = +DSitanium2,+pd,64k,+pi,64k

### Network Notes

Networking Tunable Parameters:

```
tcp_xmit_hiwater_def=2000000 Max unsent data triggers flow control(32768)
tcp_conn_request_max=2048 Max outstanding connection reqs (20)
socket_caching_tcp=4096 Size of the socket cache (512)
```

Gigabit Tunable Parameters:

```
send_max_bufs=128 Number of sending buffers consumed to trigger interrupt (16)
```

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

## Notes/Tuning Information (Continued)

### Network Notes (Continued)

recv\_max\_bufs=128 Number of receiving buffers consumed to trigger interrupt (1)  
send\_coal\_ticks=5000 Number of ticks to wait to trigger interrupt (0)  
recv\_coal\_ticks=12000 Number of ticks to wait to trigger interrupt (0)

### Client Notes

Client code generated with ./configure --enable-posix-threads  
HP-UX Tunable Parameters:  
max\_thread\_proc=800 Number of threads per process (64)  
maxfiles=2048 Soft File Limit Per Process (60)  
maxusers=256 Value of MAXUSERS macro (32)  
ncallout=5000 Increase number of pending timeouts  
nfile=4096 Max number of open files (790)  
ninode=5000 Max Number of Open Inodes (444)  
nkthread=8000 Maximum number of system-wide threads (499)

### Other Notes

Tuning Disclosure: HP-20030626.txt  
Dynamic API: HP-20020723.-API.tar.gz