

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems: Sun Fire V40z
Zeus Technology Ltd.: Zeus Web Server 4.2r4 (64 bit)

SPECweb99_SSL =5005

Test Date: Feb-2005
Tester: Sun Microsystems

Hardware Avail: Apr-2005 OS Avail: Nov-2003 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Aug-2004 SPEC license #: 6

Hardware

Vendor: Sun Microsystems
Model: Sun Fire V40z
Processor: AMD Opteron 852, 2.6 GHz
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1MB on chip
Other Cache: none
Memory: 24 GB DDR400
Disk Subsystem: 3 x 73GB Internal ULTRA320 SCSI
Disk Controllers: Onboard SCSI
Other Hardware: 2 Cisco Systems Catalyst 3750G-24T Switch

Software

Operating System: SuSE Linux Enterprise Server 8 for AMD64 SP3
File System: ext2
Other Software: Sun Fire V20z and Sun Fire V40z Servers
- bcm5700 driver ver. 7.1.22
- lsi (Fusion MPT SCSI) driver ver. 2.05.16

HTTPS Software

Vendor: Zeus Technology Ltd.
HTTPS Software: Zeus Web Server 4.2r4 (64 bit)
API: Zeus PEPP 0.9pre1 ISAPI for Dynamic content
Server Cache: none
Log Mode: Zeus Binary CLF

Test Sponsor

Test Date: Feb-2005
Tested By: Sun Microsystems
SPEC License: 6

Network

of Controllers: 4
Network Controllers: Intel Pro/1000 MT Single Port Server Adapter
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 32
Model: Ultra 60
Processor: 450MHz UltraSPARC II
of Processors: 2
Memory: 512MB
Network Controller: Sun GigaSwift Ethernet
Operating System: Solaris 9 12/03
Compiler: Sun Workshop 6 update 2 C 5.3

Notes/Tuning Information

SUT Notes

- 1 U320 10K 73GB SCSI disk for OS, and swap
- 1 U320 10K 73GB SCSI disk for fileset and post log

- 1 U320 10K 73GB SCSI disk for access log

Operating System Notes

One NIC irq bound per CPU
timer irq bound to CPU 3, onboard LSI irq bound to CPU4
ulimit -n 110490, sets number of open files, default 1024
Each NIC's TX queue length set to 20000 via ifconfig, default 100
log, & fileset partitions mounted with 'noatime, nodiratime', no inode access time updating
net.ipv4.ip_forward = 0
net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
net.core.wmem_default = 10000000, default send socket buffer size, default 65535
net.core.optmem_max = 10000000, default 10240
net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
net.ipv4.tcp_mem = 30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
net.core.netdev_max_backlog = 300000, number of unprocessed input packets before kernel starts dropping them, default 300
fs.file-max = 442961, maximum number of open files, default 1024

For more
Information
Contact

SPEC

info@spec.org
http://www.spec.org

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

Zeus Configuration
runningsite/wstest: bindaddr IP addr. 1 IP addr. 2 IP addr. 3 IP addr. 4
global.cfg:
tuning!bind_any no
tuning!unique_bind yes
tuning!cache_cooling_time 0
tuning!cache_files 282011
tuning!cache_flush_interval 31536000
tuning!cache_small_file 10000
tuning!cache_large_file 1048576
tuning!cache_max_bytes 17179869184
tuning!cache_stat_expire 31536000
tuning!cbuff_size 65536
tuning!clientfirst_optimise yes
tuning!keepalive yes
tuning!keepalive_max -1
tuning!keepalive_timeout 3600
tuning!listen_queue_size 8192
tuning!maxaccept 2048
tuning!modules!cgi!cleansize 0
tuning!sendfile no
tuning!sendfile_minsize 0
tuning!sendfile_maxsize 0
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 2617
tuning!ssl_cbuff_size 32840
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!modules!isapi!enabled no

HTTP API Notes

Zeus PEPP configured with command: ./Configure --ssl=yes
Zeus PEPP compiled with default gcc (v3.2.2-4)

Client Notes

set sq_max_size=0, set hires_tick=1
nnd -set /dev/tcp tcp_smallest_anon_port 2048
nnd -set /dev/tcp tcp_time_wait_interval 60000
Client code generated with: CFLAGS=-xO4 -xchip=ultra -xarch=v8plusa
./configure --enable-posix-threads --enable-gethostbyname_r --enable-pthread_scope_system --enable-rlimit --enable-safe-usleep=no

Other Notes

Tuning Disclosure: See above.
Dynamic API: HP-20020724-API.tgz
Client Tuning Disclosure: Sun-20020610.txt
2 Cisco Systems Catalyst 3750G-24T Switch used for 4 networks