



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel VC820(850 MHz Pentium III processor)

SPECint2000 = 367
SPECint_base2000 = 366

SPEC license #: 13 Tested by: Intel Corporation Test date: Jun-2000 Hardware Avail: Mar-2000 Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	323	434	323	434
175.vpr	1400	497	281	498	281
176.gcc	1100	344	320	344	320
181.mcf	1800	735	245	735	245
186.crafty	1000	225	445	225	445
197.parser	1800	614	293	614	293
252.eon	1300	314	414	314	414
253.perlbmk	1800	358	502	358	502
254.gap	1100	302	364	302	364
255.vortex	1900	315	604	311	611
256.bzip2	1500	469	320	455	330
300.twolf	3000	957	314	948	317

Hardware

CPU: Pentium III processor (850 MHz, 100 MHz bus)
CPU MHz: 850
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 16KBI + 16KBD on-die
Secondary Cache: 256KB(I+D) on-die ECC
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB PC800 RDRAM
Disk Subsystem: IBM DTLA 307030 ATA-66+
Other Hardware: Creative Labs Annihilator Pro GeForce 256 DDR

Software

Operating System: Windows 2000(Build 2195)
Compiler: Intel C++ and Fortran Compiler 5.0, for Windows NT 4.0/Windows 2000, Microsoft Visual C++ 6.0 (for libraries), SmartHeap library V5.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxK -Qipo_wp shlw32M.lib +FDO
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability flags:
175.vpr: -Op          176.gcc: -Dalloca=_alloca /F10000000 -Op
186.crafy: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip, 175.vpr, 176.gcc, 181.mcf, 186.crafty, 197.parser, 252.eon, 253.perlbmk, 254.gap:
-QxK -Qipo_wp +FDO shlw32M.lib
255.vortex, 256.bzip2, 300.twolf:
-QxK -Qipo_wp +FDO -Oa shlw32M.lib
Tested systems can be used with Shin-G ATX case, Sparkle Inc. power supply
Product description as of 06/2000:
http://developer.intel.com/design/motherbd/vc/
Motherboard available through Intel OEM Distribution channel. See
http://channel.intel.com/ for more information
The system bus runs at 100 MHz
```