CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.7 GHz, Pentium 4 processor)

SPECfp2000 = 608

SPECfp_base2000 = 598

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Apr-2001 | Hardware Avail: Apr-2001 | Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	186	858	186	858
171.swim	3100	242	1281	242	1282
172.mgrid	1800	294	612	272	662
173.applu	2100	294	714	293	716
177.mesa	1400	220	635	226	621
178.galgel	2900	501	579	501	579
179.art	2600	496	525	482	539
183.equake	1300	164	791	146	889
187.facerec	1900	377	504	376	506
188.ammp	2200	568	387	564	390
189.lucas	2000	239	836	239	836
191.fma3d	2100	444	473	444	473
200.sixtrack	1100	380	290	375	293
301.apsi	2600	568	457	568	458



Hardware

CPU:	Pentium 4 processor (1.7 GHz, 400 MHz bus)
CPU MHz:	1700
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 8KBD
Secondary Cache:	256KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	256 MB (2 128 MB PC800 RDRAM non-ECC modules)
Disk Subsystem:	IBM DTLA-307030 ATA-100
Other Hardware:	Creative Labs Annihalator 2

Software

Operating System:	Windows 2000 (Build 2195) Service Pack 1
Compiler:	Intel C/C++ Compiler 5.0 Build 001120 Intel Fortran Compiler 5.0 Build 001027 Microsoft Visual C++ 6.0 (for libraries) Other software: Microquill SmartHeap V5.0
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning:  -Qipo -QxW -O3 +FDO
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -Qipo -QxW  -O3 +FDO
171.swim:     -Qipo -QxW  -O3 +FDO
172.mgrid:    -Qipo -QaxW -O3 +FDO
173.applu:    -Qipo -QxW  -O3 +FDO
177.mesa:     -Qipo -QxW  -Oa -O3 +FDO
178.galgel:   -Qipo -QxW  -O3 +FDO
179.art:      -Qipo -QxW  -O3 -Oa +FDO shlW32M.lib
183.equake:   -Qipo -QxW  -Qrcd -Oa +FDO shlW32M.lib
187.facerec:  -Qipo -QxW  -O3 +FDO shlW32M.lib
188.ammp:     -Qipo -Oa -QxW -O3 +FDO
189.lucas:    -Qipo -QxW  -O3 +FDO
191.fma3d:    -Qipo -QxW  -O3 +FDO
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
200.sixtrack: -Qipo -QxW  +FDO
301.apsi:     -Qipo -QxW  -O3 +FDO
Library ordering for 187.facerec (include SmartHeap correctly with default libs):
LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlW32M.lib
     LIBC.lib libirc.lib OLDNAMES.lib
shlW32M.lib is the SmartHeap library V5.0 from Microquill: http://www.microquill.com
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply
Product description located as of 11/2000:
http://developer.intel.com/design/motherbd/gb/gb_ds.htm
Motherboard is available through Intel OEM Distribution Channel. See
http://channel.intel.com/business/ibp/boards/d850gb.htm for more information
The system bus runs at 400 MHz
```