CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer GS80 Model 8 68/1001

SPECint2000 = 621

SPECint_base2000 = 561

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	300	466	297	471
175.vpr	1400	290	482	289	485
176.gcc	1100	173	636	148	745
181.mcf	1800	481	374	353	509
186.crafty	1000	124	803	124	803
197.parser	1800	445	405	347	519
252.eon	1300	163	798	159	818
253.perlbmk	1800	298	605	285	633
254.gap	1100	356	309	291	378
255.vortex	1900	253	752	223	852
256.bzip2	1500	248	606	232	647
300.twolf	3000	366	821	356	843



Hardware

CPU:	Alpha 21264C
CPU MHz:	1001
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1 to 8
Parallel:	No
Primary Cache:	64KB(I)+64KB(D) on chip
Secondary Cache:	8MB off chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	16GB
Disk Subsystem:	mfs (Memory File System)
Other Hardware:	None

Software

Operating System:	Tru64 UNIX V5.1 +Patch Kit 2
Compiler:	Compaq C V6.4-214-46B59 Program Analysis Tools V2.0 Spike V5.2 DTK (1.461 46B5P) Compaq C++ V6.3-010-46B2F
File System:	mfs
System State:	Multi-user

Notes/Tuning Information

```
Baseline C  : cc  -arch ev6 -fast +CFB ONESTEP
         C++: cxx -arch ev6 -O2        ONESTEP

Peak:
  All but 252.eon: cc -g3 -arch ev6 ONESTEP
     164.gzip: -fast -O4 -non_shared +CFB
      175.vpr: -fast -O4 -assume restricted_pointers +CFB
      176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
               +CFB +IFB
      181.mcf: -fast -xtaso_short +CFB +IFB +PFB
   186.crafty: same as base
   197.parser: -fast -O4 -xtaso_short -non_shared +CFB
      252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
  253.perlbmk: -fast -non_shared +CFB +IFB
      254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
   255.vortex: -fast -non_shared +CFB +IFB
    256.bzip2: -fast -O4 -non_shared +CFB
    300.twolf: -fast -O4 -assume restricted_pointers -all
               -ldensemalloc -none +CFB +IFB
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use       -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA perlbmk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64 gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO -DSPEC_CPU2000_LP64

Information on UNIX V5.1 Patches can be found at http://ftp1.service.digital.com/public/unix/v5.1/

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, http://www.tru64unix.compaq.com/dtk/ . The features used in this SPEC submission will be available at the web site as a beta kit in August, 2001, and as a production release in October, 2001. The C compiler for this SPEC submission has been

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
available at the same location, as a production release, since
May, 2001.

Sysconfigtab settings:
            max_proc_per_user = 4096
         max_threads_per_user = 4096
       per_proc_data_size     = 21474836480
   max_per_proc_data_size     = 21474836480
       per_proc_address_space = 21474836480
   max_per_proc_address_space = 21474836480
```