CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer DS20E Model 68/833

SPECint_rate2000 = 13.1

SPECint_rate_base2000 = 12.0

SPEC license #: 2 | Tested by: Compaq NH | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Aug-2001



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	357	9.10	2	352	9.22
175.vpr	2	319	10.2	2	317	10.2
176.gcc	2	189	13.5	2	167	15.3
181.mcf	2	393	10.6	2	303	13.8
186.crafty	2	149	15.5	2	149	15.5
197.parser	2	499	8.37	2	406	10.3
252.eon	2	194	15.5	2	191	15.8
253.perlbmk	2	348	12.0	2	324	12.9
254.gap	2	307	8.31	2	261	9.78
255.vortex	2	273	16.2	2	247	17.9
256.bzip2	2	275	12.6	2	256	13.6
300.twolf	2	443	15.7	2	432	16.1

Hardware

CPU:	Alpha 21264B
CPU MHz:	833
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1 to 2
Parallel:	No
Primary Cache:	64KB(I)+64KB(D) on chip
Secondary Cache:	8MB off chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	4GB
Disk Subsystem:	1x18GB
Other Hardware:	None

Software

Operating System:	Tru64 UNIX V5.1 +Patch Kit 2
Compiler:	Compaq C V6.4-214-46B59 Program Analysis Tools V2.0 Spike V5.2 DTK (1.461 46B5P) Compaq C++ V6.3-010-46B2F
File System:	AdvFS
System State:	Multi-user

Notes/Tuning Information

```
Baseline C  : cc  -arch ev6 -fast +CFB ONESTEP
         C++: cxx -arch ev6 -O2        ONESTEP
Peak:
  All but 252.eon: cc -g3 -arch ev6 ONESTEP
     164.gzip: -fast -O4 -non_shared +CFB
      175.vpr: -fast -O4 -assume restricted_pointers +CF
      176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc
               +CFB +IFB
      181.mcf: -fast -xtaso_short +CFB +IFB +PFB
   186.crafty: same as base
   197.parser: -fast -O4 -xtaso_short -non_shared +CFB
      252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -non
  253.perlbmk: -fast -non_shared +CFB +IFB
      254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
   255.vortex: -fast -non_shared +CFB +IFB
    256.bzip2: -fast -O4 -non_shared +CFB
    300.twolf: -fast -O4 -assume restricted_pointers -al
               -ldensemalloc -none +CFB +IFB
Most benchmarks are built using one or more types of
profile-driven feedback.  The types used are designated
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
by abbreviations in the notes:
+CFB: Code generation is optimized by the compiler, usin
      feedback from a training run.  These commands are
      done before the first compile (in phase "fdo_pre0"
           mkdir /tmp/pp
           rm -f /tmp/pp/${baseexe}*
      and these flags are added to the first and second
           PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp
           PASS2_CFLAGS = -prof_use       -prof_dir /tmp
     (Peak builds use /tmp/pp above; base builds use /tm
+IFB: Icache usage is improved by the post-link-time opt
      Spike, using feedback from a training run.  These
      are used (in phase "fdo_postN"):
           mv ${baseexe} oldexe
           spike oldexe -feedback oldexe -o ${baseexe}
+PFB: Prefetches are improved by the post-link-time opti
      Spike, using feedback from a training run.  These
      commands are used (in phase "fdo_post_makeN"):
           rm -f *Counts*
           mv ${baseexe} oldexe
           pixie -stats dstride oldexe 1>pixie.out 2>pix
           mv oldexe.pixie ${baseexe}
      A training run is carried out (in phase "fdo_runN"
      then this command (in phase "fdo_postN"):
           spike oldexe -fb oldexe -stride_prefetch -o $
When Spike is used for both Icache and Prefetch improvem
only one spike command is actually issued, with the Icac
options followed by the Prefetch options.
Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DA
perlbmk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL
     -DSPEC_CPU2000_LP64
Information on UNIX V5.1 Patches can be found at
http://ftp1.service.digital.com/public/unix/v5.1/
Spike, and the Program Analysis Tools, are part of the D
Tool Kit Supplement, http://www.tru64unix.compaq.com/dtk
features used in this SPEC submission will be available
site as a beta kit in August, 2001, and as a production
October, 2001.  The C compiler for this SPEC submission
available at the same location, as a production release,
May, 2001.
```