



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 1X 500MHz R14k

SPECint2000 = **412**
SPECint_base2000 = **397**

SPEC license #: 4 Tested by: SGI Test date: May-2001 Hardware Avail: Jul-2001 Software Avail: May-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	527	266	508	276	
175.vpr	1400	305	460	293	478	
176.gcc	1100	300	367	299	368	
181.mcf	1800	297	607	297	607	
186.crafty	1000	245	409	244	410	
197.parser	1800	526	342	500	360	
252.eon	1300	300	433	280	465	
253.perlbnk	1800	590	305	591	305	
254.gap	1100	455	242	453	243	
255.vortex	1900	334	569	295	643	
256.bzip2	1500	372	404	331	453	
300.twolf	3000	543	552	543	552	

Hardware

CPU: R14000
 CPU MHz: 500
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 2-8
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 1 GB
 Disk Subsystem: 1 x 18 GB FC, 4 x 18 GB FC (striped)
 Other Hardware: None

Software

Operating System: IRIX 6.5.12f
 Compiler: MIPSpro 7.3.1.2m C, C++
 SCSSL 1.3 Math Library
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)
 PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -DUSG -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSGI
 252.eon: -lm
 253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
 -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
 300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)
 175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
 . -LNO:prefetch Ahead=2 -INLINE:aggressive=on
 . -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld_latency=10 -lmalloc (FEEDBACK)
 181.mcf: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 1X 500MHz R14k

SPECint2000 =	412
SPECint_base2000 =	397

SPEC license #:	4	Tested by:	SGI	Test date:	May-2001	Hardware Avail:	Jul-2001	Software Avail:	May-2001
-----------------	---	------------	-----	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
. (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
. -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
. -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
. -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak

```

The first disk mentioned in the Disk Subsystem is the system disk. A striped XFS filesystem was created using the rest of the disks and the benchmark was run on this.