CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard (1.8 GHz, Pentium 4 processor)

SPECint2000 = 613

SPECint_base2000 = 598

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Aug-2001 | Hardware Avail: Jul-2001 | Software Avail: Jun-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	214	654	214	655
175.vpr	1400	429	327	404	347
176.gcc	1100	172	640	172	640
181.mcf	1800	357	504	357	504
186.crafty	1000	172	582	171	584
197.parser	1800	325	553	325	554
252.eon	1300	158	822	135	961
253.perlbmk	1800	214	841	214	840
254.gap	1100	133	825	131	838
255.vortex	1900	234	810	224	849
256.bzip2	1500	307	488	304	493
300.twolf	3000	714	420	713	421



Hardware

CPU:	Pentium 4 processor (1.8 GHz, 400 MHz bus)
CPU MHz:	1800
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 8KBD on chip
Secondary Cache:	256KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	256 MB (2 128 MB PC800 RDRAM non-ECC modules)
Disk Subsystem:	IBM DTLA-307030 ATA-100
Other Hardware:	None

Software

Operating System:	Windows 2000(Build 2195, SP2)
Compiler:	Intel C++ Compiler 5.0.1 Build 010525Z Microsoft Visual C++ 6.0 SP5(for libraries) MicroQuill SmartHeap library V6.0
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -QxW -Qipo shlW32M.lib +FDO
Base tuning for C++ programs: -QxW -Qipo -GX -GR
shlW32M.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip:     -QxW -Qipo -Oa shlW32M.lib +FDO
175.vpr:      -QxW -Qwp_ipo +FDO
176.gcc:      -QxW -Qipo shlW32M.lib +FDO
181.mcf:      -QxW -Qipo shlW32M.lib +FDO
186.crafty:   -QxW -Qipo -Oa shlW32M.lib +FDO
197.parser:   -QxW -Qipo shlW32M.lib +FDO
252.eon:      -QxW -Qipo +FDO
253.perlbmk:  -QxW -Qipo shlW32M.lib +FDO
254.gap:      -QxW -Qipo +FDO
255.vortex    -QxW -Qwp_ipo -Oa shlW32M.lib +FDO
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
256.bzip2:    -QxW -Qipo -Oa +FDO
300.twolf:    -QxW -Qipo shlW32M.lib +FDO
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B
Product description located as of 11/2000:
http://developer.intel.com/design/motherbd/gb/gb_ds.htm
Motherboard is available through Intel OEM Distribution Channel. See
http://channel.intel.com/business/ibp/boards/d850gb.htm for more information
The system bus runs at 400 MHz
```