CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D815EEA2 motherboard (933 MHz, Pentium III processor)

SPECint2000 = 428

SPECint_base2000 = 421

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Aug-2001 | Hardware Avail: Aug-2001 | Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	316	444	311	451
175.vpr	1400	404	347	404	346
176.gcc	1100	336	327	337	327
181.mcf	1800	618	291	618	291
186.crafty	1000	208	480	208	480
197.parser	1800	526	342	526	342
252.eon	1300	227	573	202	645
253.perlbmk	1800	318	565	318	565
254.gap	1100	263	418	263	418
255.vortex	1900	280	680	275	692
256.bzip2	1500	404	371	392	383
300.twolf	3000	788	381	786	382



Hardware

CPU:	Pentium III processor (933 MHz, 133 MHz bus)
CPU MHz:	933
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	16KBI + 16KBD on chip
Secondary Cache:	256KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	128 MB PC133 CL2 SDRAM (2 * 128 MB sticks)
Disk Subsystem:	IBM DTLA-307030 ATA-100
Other Hardware:	None

Software

Operating System:	Windows 2000 (Build 2195, SP1)
Compiler:	Intel C++ Compiler 5.0 for Windows Build 001120 Microsoft Visual C++ 6.0(for libraries) MicroQuill SmartHeap V5.0
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -QxK -Qipo shlW32M.lib +FDO
Base tuning for C++ programs: -QxK -Qipo -GX -GR
shlW32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip, 175.vpr, 176.gcc, 181.mcf, 186.crafty, 197.parser, 253.perlbmk, 254.gap:
-QxK -Qipo FDO shlW32M.lib
 255.vortex, 256.bzip2, 300.twolf:
-QxK -Qipo FDO -Oa shlW32M.lib
 252.eon:
-QxK -Qipo +FDO
Tested systems can be used with Shin-G ATX case, Nspire MAV-250P power supply.
Product information as of 08/2001:
http://developer.intel.com/design/motherbd/ea2/index.htm
Motherboard is available through Intel OEM Distribution Channel.
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

See http://channel.intel.com/ for more information
The system bus runs at 133 MHz