



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 610 Mod 6C1 375MHz

SPECfp2000 = 372

SPECfp_base2000 = 368

SPEC license #: 11 Tested by: IBM Corp. Test date: Sep-2001 Hardware Avail: Oct-2001 Software Avail: Dec-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	313	511	313	511	
171.swim	3100	778	399	778	399	
172.mgrid	1800	614	293	614	293	
173.applu	2100	683	307	680	309	
177.mesa	1400	526	266	513	273	
178.galgel	2900	366	792	366	792	
179.art	2600	355	732	355	732	
183.earthquake	1300	263	495	244	533	
187.facerec	1900	489	388	489	388	
188.amp	2200	746	295	747	294	
189.lucas	2000	765	261	745	268	
191.fma3d	2100	674	312	649	324	
200.sixtrack	1100	519	212	519	212	
301.apsi	2600	861	302	861	302	

Hardware

CPU: POWER3-II
CPU MHz: 375
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI+64KBD (on chip)
Secondary Cache: 4MB unified (off chip)
L3 Cache: None
Other Cache: None
Memory: 2GB
Disk Subsystem: 2x18GB 10000RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.1
Compiler: Fortran 77 and 90: IBM xl Fortran 7.1.1.0 invoked as 'xlf90' for Fortran 90 and as xlf for Fortran 77
C: IBM VAC++ 5.0.2.0 invoked as 'xlc'
File System: AIX/JFS
System State: Multi-user

Notes/Tuning Information

Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:

Fortran: -O5 -lmass
C: -O5 -lmass

Peak Optimization Flags

168.wupwise: (basepeak=1)
171.swim: (basepeak=1)
172.mgrid: (basepeak=1)
173.applu: -O5 -lmass -qipa=partition=large
177.mesa: -O5 -lmass -qipa=partition=large, fdpr -v -R3
178.galgel: (basepeak=1)
179.art: (basepeak=1)
183.earthquake: -O5 -lmass -lhmu -qinline
187.facerec: (basepeak=1)
188.amp: -O3 -qarch=pwr3



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 610 Mod 6C1 375MHz

SPECfp2000 = 372

SPECfp_base2000 = 368

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```
189.lucas: -qpdf1/pdf2 -O3 -lhm -lmas
           -qipa=partition=large, fdpr -v -R3
191.fma3d: -O4 -lmas -qipa=partition=large
200.sixtrack: (basepeak=1)
301.apsi: (basepeak=1)
fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O
APAR IY 21957 was applied to AIX 5L V5.1 to enable new hardware support
```