# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D850MD motherboard (1.6 GHz, Pentium 4 processor)

SPECfp2000 = 637

SPECfp_base2000 = 626

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Nov-2001 | Hardware Avail: Aug-2001 | Software Avail: Oct-2001

| Benchmark | Reference Time | Base Runtime | Base Ratio | Runtime | Ratio |
|---|---|---|---|---|---|
| 168.wupwise | 1600 | 195 | 821 | 193 | 829 |
| 171.swim | 3100 | 249 | 1243 | 246 | 1259 |
| 172.mgrid | 1800 | 296 | 607 | 283 | 635 |
| 173.applu | 2100 | 299 | 702 | 291 | 721 |
| 177.mesa | 1400 | 215 | 652 | 212 | 659 |
| 178.galgel | 2900 | 361 | 804 | 356 | 814 |
| 179.art | 2600 | 500 | 520 | 489 | 532 |
| 183.equake | 1300 | 181 | 719 | 172 | 757 |
| 187.facerec | 1900 | 266 | 714 | 265 | 716 |
| 188.ammp | 2200 | 594 | 370 | 586 | 375 |
| 189.lucas | 2000 | 229 | 873 | 229 | 873 |
| 191.fma3d | 2100 | 391 | 537 | 390 | 538 |
| 200.sixtrack | 1100 | 375 | 294 | 362 | 303 |
| 301.apsi | 2600 | 563 | 462 | 562 | 463 |




### Hardware

| | |
|---|---|
| CPU: | Pentium 4 processor (1.6 GHz, 400 MHz bus) |
| CPU MHz: | 1600 |
| FPU: | Integrated |
| CPU(s) enabled: | 1 core, 1 chip, 1 core/chip |
| CPU(s) orderable: | 1 |
| Parallel: | No |
| Primary Cache: | 12k micro-ops I + 8KBD on chip |
| Secondary Cache: | 256KB(I+D) on chip |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 256 MB (2 128 MB PC800 RDRAM non-ECC modules) |
| Disk Subsystem: | IBM DTLA-307030 ATA-100 |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | Windows XP Professional(Build 2600) |
| Compiler: | Intel C++ Compiler 5.0.1 Build 010525Z<br>Intel Fortran Compiler 5.0.1 Build 010525Z<br>Microsoft Visual C++ 6.0 SP5(for libraries) |
| File System: | FAT32 |
| System State: | Default |

## Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning:  -Qipo -QxW -O3 +FDO
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -Qipo -QxW  -O3 +FDO
171.swim:     -Qipo -QxW  -O3 +FDO
172.mgrid:    -Qipo -QaxW -O3 +FDO
173.applu:    -Qipo -QxW  -O3 -Qscalar_rep- -Qauto +FDO
177.mesa:     -Qipo -Oa -QxW -O3 +FDO
178.galgel:   -Qipo -QxW  -O3 +FDO
179.art:      -Qipo -QxW  -O3 -Oa +FDO
183.equake:   -Qipo -QxW  -Oa -Qrcd +FDO
187.facerec:  -Qipo -QxW  -O3 +FDO
188.ammp:     -Qipo -QxW  -O3 -Oa +FDO
189.lucas:    -Qipo -QxW  -O3 +FDO
191.fma3d:    -Qipo -QxW  -O3 +FDO
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
200.sixtrack: -Qipo -QxW  +FDO
301.apsi:     -Qipo -QxW  -O3 +FDO
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B
Product description located as of 1/2002:
http://developer.intel.com/design/motherbd/md/index.htm
Motherboard ordering information is available at:
http://program.intel.com/shared/products/boards/D850MD/index.htm
The system bus runs at 400 MHz
```