CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer DS20L Model 68/833

SPECint_rate2000 = 6.23

SPECint_rate_base2000 = 5.61

SPEC license #: 2 | Tested by: Compaq NH | Test date: Feb-2002 | Hardware Avail: Mar-2002 | Software Avail: Oct-2001



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	351	4.63	1	345	4.70
175.vpr	1	340	4.78	1	339	4.79
176.gcc	1	202	6.31	1	177	7.21
181.mcf	1	609	3.43	1	424	4.92
186.crafty	1	145	8.03	1	145	8.03
197.parser	1	553	3.77	1	428	4.88
252.eon	1	194	7.79	1	190	7.93
253.perlbmk	1	358	5.83	1	324	6.44
254.gap	1	310	4.12	1	259	4.93
255.vortex	1	291	7.57	1	262	8.40
256.bzip2	1	290	6.00	1	270	6.45
300.twolf	1	443	7.86	1	433	8.04

Hardware

CPU:	Alpha 21264B
CPU MHz:	833
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1 to 2
Parallel:	No
Primary Cache:	64KB(I)+64KB(D) on chip
Secondary Cache:	4MB off chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	2GB
Disk Subsystem:	1x40GB Maxtor 5T040H4
Other Hardware:	None

Software

Operating System:	Tru64 UNIX V5.1A (rev. 1885)
Compiler:	Compaq C V6.4-215-46B7O Program Analysis Tools V2.0 Spike V5.2 DTK (1.471.2.2 46B5P) Compaq C++ V6.3-010-46B2F
File System:	AdvFS
System State:	Multi-user

Notes/Tuning Information

```
Baseline C  : cc  -arch ev6 -fast +CFB ONESTEP
         C++: cxx -arch ev6 -O2        ONESTEP

Peak:
  All but 252.eon: cc -g3 -arch ev6 ONESTEP
     164.gzip: -fast -O4 -non_shared +CFB
      175.vpr: -fast -O4 -assume restricted_pointers +CFB
      176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
               +CFB +IFB
      181.mcf: -fast -xtaso_short +CFB +IFB +PFB
   186.crafty: same as base
   197.parser: -fast -O4 -xtaso_short -non_shared +CFB
      252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
  253.perlbmk: -fast -non_shared +CFB +IFB
      254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
  255.vortex: -fast -non_shared +CFB +IFB
    256.bzip2: -fast -O4 -non_shared +CFB
    300.twolf: -fast -O4 -assume restricted_pointers -all
               -ldensemalloc -none +CFB +IFB
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Most benchmarks are built using one or more types of
profile-driven feedback.  The types used are designated
by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using
      feedback from a training run.  These commands are
      done before the first compile (in phase "fdo_pre0"):

           mkdir /tmp/pp
           rm -f /tmp/pp/${baseexe}*

      and these flags are added to the first and second compiles:

           PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
           PASS2_CFLAGS = -prof_use       -prof_dir /tmp/pp

     (Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer
      Spike, using feedback from a training run.  These commands
      are used (in phase "fdo_postN"):

           mv ${baseexe} oldexe
           spike oldexe -feedback oldexe -o ${baseexe}

+PFB: Prefetches are improved by the post-link-time optimizer
      Spike, using feedback from a training run.  These
      commands are used (in phase "fdo_post_makeN"):

           rm -f *Counts*
           mv ${baseexe} oldexe
           pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
           mv oldexe.pixie ${baseexe}

      A training run is carried out (in phase "fdo_runN"), and
      then this command (in phase "fdo_postN"):

           spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}

When Spike is used for both Icache and Prefetch improvements,
only one spike command is actually issued, with the Icache
options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbmk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
     -DSPEC_CPU2000_LP64

Spike, and the Program Analysis Tools, are part of the Developers'
Tool Kit Supplement, http://www.tru64unix.compaq.com/dtk/ .  The
features used in this SPEC submission will be available at the web
site as a production release as of October, 2001.  The C compiler for
this SPEC submission has been available at the same location, as a
production release, since August 15, 2001.
```