



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

MSI K7D Master-L Motherboard, AMD Athlon (TM) MP 2100+

SPECint_rate2000 = 8.27

SPECint_rate_base2000 = 7.97

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Jun-2002 | Hardware Avail: Jun-2002 | Software Avail: Feb-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	163	9.97	1	162	10.0
175.vpr	1	333	4.87	1	309	5.25
176.gcc	1	240	5.31	1	204	6.25
181.mcf	1	610	3.42	1	610	3.42
186.crafty	1	98.3	11.8	1	98.3	11.8
197.parser	1	294	7.09	1	294	7.11
252.eon	1	93.0	16.2	1	84.1	17.9
253.perlbnk	1	172	12.1	1	172	12.1
254.gap	1	141	9.07	1	140	9.08
255.vortex	1	173	12.8	1	170	13.0
256.bzip2	1	267	6.52	1	253	6.87
300.twolf	1	578	6.02	1	568	6.12

Hardware

CPU: AMD Athlon (TM) MP 2100+
CPU MHz: 1733
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2x256MB PC2100 DDR SDRAM CL2
Disk Subsystem: Seagate ST318451LW
Other Hardware: None

Software

Operating System: Windows 2000 SP2
Compiler: Intel C++ 5.0.1 build 020125Z
Microsoft Visual Studio 6.0 SP5 (libraries)
MicroQuill SmartHeap Library 5.0
File System: FAT32
System State: Default

Notes/Tuning Information

shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -QxK -Qipo +FDO shlw32M.lib

Baseline C++: -QxK -Qipo -GX -GR

Peak tuning:

164.gzip: -O3 -QxK -Qwp_ipo -Oi- -Oa +FDO

175.vpr: -O3 -Qxi -QaxK -Qwp_ipo +FDO

176.gcc: -O3 -QxK -Qwp_ipo -Oi- +FDO shlw32M.lib

181.mcf: -O3 -QxK -Qwp_ipo +FDO shlw32M.lib

186.crafty: -O3 -QxK -Qwp_ipo -Oa +FDO shlw32M.lib

197.parser: -O3 -QxK -Qwp_ipo +FDO

252.eon: -O3 -QxK -Qwp_ipo +FDO

253.perlbnk: -O3 -QxK -Qipo +FDO shlw32M.lib

254.gap: -O3 -QxK -Qipo -Oi- +FDO

255.vortex: -O3 -QxK -Qwp_ipo +FDO

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

MSI K7D Master-L Motherboard, AMD Athlon (TM) MP 2100+

SPECint_rate2000 = 8.27

SPECint_rate_base2000 = 7.97

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Jun-2002 | Hardware Avail: Jun-2002 | Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```
256.bzip2:    -O3 -QxK -Oa -Qwp_ipo
300.twolf:    -O3 -QxK -Qipo -Oa +FDO shlw32M.lib
ONESTEP is used for all base and peak runs
```

The tested system can be assembled using an ATX case such as the Antec KS-282, a 420W power supply such as the NSPIRE NSP-420P4B, and a PCI or AGP video card. The System bus runs at 266MHz