CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480

SPECint_rate2000 = 12.2

SPECint_rate_base2000 = 10.7

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: May-2002 | Hardware Avail: Jun-2002 | Software Avail: May-2002



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	381	8.52	2	346	9.38
175.vpr	2	354	9.18	2	317	10.2
176.gcc	2	224	11.4	2	191	13.3
181.mcf	2	358	11.7	2	290	14.4
186.crafty	2	199	11.6	2	168	13.8
197.parser	2	426	9.79	2	343	12.2
252.eon	2	262	11.5	2	253	11.9
253.perlbmk	2	387	10.8	2	359	11.6
254.gap	2	345	7.41	2	343	7.45
255.vortex	2	298	14.8	2	230	19.2
256.bzip2	2	276	12.6	2	264	13.2
300.twolf	2	596	11.7	2	530	13.1

Hardware

CPU:	UltraSPARC III Cu
CPU MHz:	900
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	2,4
Parallel:	No
Primary Cache:	32KBI+64KBD on chip per CPU
Secondary Cache:	8MB(I+D) off chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	4GB
Disk Subsystem:	1 x 36GB + 1 x 18GB
Other Hardware:	None

Software

Operating System:	Solaris 8 02/02
Compiler:	Sun ONE Studio 7 with patch 111704-01 Sun Performance Library 7
File System:	tmpfs
System State:	Multi-User

Notes/Tuning Information

```
Portability:
 176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSUN
 252.eon: -library=iostream
 253.perlbmk: -DSPEC_CPU2000_SOLARIS
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
          -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO
Base Flags:
 Base C   flags: -fast -xcrossfile -ll2amm -xprofile
 Base C++ flags: -fast -xcrossfile -xprofile

Peak Flags:
 164.gzip: -xO5 -xtarget=native -xalias_level=std -W2,-whole -xcrossfile -W2,-Ainline -xprofile
 175.vpr: -fast -xalias_level=std -xcrossfile -xsfpconst -W2,-whole
          -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,-Qeps:rp_filtering_margin=100
          -xregs=syst -lmopt -xprofile
 176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -ll2amm -xprofile
 181.mcf: -fast -xcrossfile -Wc,-Qms_pipe-pref,-Qlp=1-fa=1-av=64-t=3-fl=1
          -lprism32 -xprofile
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 186.crafty: -fast -xF -xinline= -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4
             -xalias_level=strong -xregs=syst -W2,-Ashort_ldst,-Aivel:duplicate_loops
             -xprofile
 197.parser: -fast -xprefetch=no%auto -xcrossfile -xregs=syst
          -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong -Wc,-Qipa:valueprediction -xprofile
 252.eon: -fast -xcrossfile -xalias_level=compatible -xsafe=mem -Qoption iropt -Mt500,-xrestrict
          -Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -lmopt -xprofile
 253.perlbmk: -xO5 -xtarget=native -xcrossfile -xalias_level=std -xsafe=mem
              -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1
              -Wc,-Qinline_memcpy=32 -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1
              -Wc,-Qiselect-sw_pf_tbl_th=20 -xprofile
 254.gap: -fast -xcrossfile -xalias_level=std -xprefetch -W2,-whole -lprism32 -xprofile
 255.vortex: -fast -xcrossfile -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1
            -Wc,-Qinline_memcpy=32 -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
             -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32
             -Wc,-Qpeep-Sh0 -xrestrict -ll2amm -lprism32 -xprofile
 256.bzip2: -fast -W2,-Abopt -xcrossfile -xalias_level=strong
            -Wc,-Qiselect-funcalign=32 -xregs=syst -xprofile
 300.twolf: -fast -xalias_level=strong -xsafe=mem -xcrossfile -xprefetch=no%auto
            -Wc,-Qms_pipe+intdivusefp -xprofile
ONESTEP=yes for all benchmarks in base and peak

Shell Environments:
 LD_LIBRARY_PATH=/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb
 PRISM_HEAP=268435456
 PRISM_MODE=2

 Stack size set to unlimited via "ulimit -s unlimited"



Kernel Parameters (/etc/system):
 set shmsys:shminfo_shmmin=1
 set shmsys:shminfo_shmmax=1477846784
 set shmsys:shminfo_shmmni=256
 set shmsys:shminfo_shmseg=400

System configuration details located (as of Jun 2002) at
    http://www.sun.com/servers/entry/
```