CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480

SPECfp_rate2000 = 29.9

SPECfp_rate_base2000 = 26.1

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: May-2002 | Hardware Avail: Jun-2002 | Software Avail: May-2002



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	297	25.0	4	297	25.0
171.swim	4	498	28.9	4	498	28.9
172.mgrid	4	495	16.9	4	495	16.9
173.applu	4	824	11.8	4	403	24.2
177.mesa	4	282	23.1	4	275	23.6
178.galgel	4	206	65.2	4	168	80.0
179.art	4	31.5	383	4	31.5	383
183.equake	4	251	24.0	4	158	38.1
187.facerec	4	240	36.7	4	240	36.7
188.ammp	4	510	20.0	4	518	19.7
189.lucas	4	679	13.7	4	468	19.8
191.fma3d	4	644	15.1	4	581	16.8
200.sixtrack	4	482	10.6	4	482	10.6
301.apsi	4	554	21.8	4	554	21.8

Hardware

CPU:	UltraSPARC III Cu
CPU MHz:	900
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	2,4
Parallel:	No
Primary Cache:	32KBI+64KBD on chip per CPU
Secondary Cache:	8MB(I+D) off chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	8GB
Disk Subsystem:	1 x 36GB + 1 x 18GB
Other Hardware:	None

Software

Operating System:	Solaris 8 02/02
Compiler:	Sun ONE Studio 7 with patch 111704-01 Sun Performance Library 7
File System:	tmpfs
System State:	Multi-User

Notes/Tuning Information

```
Portability:
 178.galgel: -e -fixed

Base Flags:
 Base C flags: -fast -xipo=2 -xalias_level=std -xprofile
 Base F90 flags: -fast -xcrossfile -lprism32 -xprofile

Peak Flags:
 168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: -fast -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
            -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1
            -Qoption f90comp -O3
 177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
 178.galgel: -fast -xcrossfile -xregs=syst -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf -xprofile
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 179.art: basepeak=yes
 183.equake: -fast -xalias_level=strong -W2,-whole,-Amemopt:arrayloc
             -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -xprofile
 187.facerec: basepeak=yes
 188.ammp: -fast -xcrossfile -xalias_level=std -lprism32 -xprofile
 189.lucas: -fast -Qoption f90comp -array_pad_rows,2002 -Qoption iropt -whole
            -Qoption cg -Qms_pipe-pref,-Qlp=1-t=3-fa=1
            -lprism32 -xprofile
 191.fma3d: -fast -xcrossfile -stackvar -Qoption cg -Qlp=1-av=256-t=3-fa=1 -xprofile
 200.sixtrack: basepeak=yes
 301.apsi: -fast -Qoption iropt -Mt450 -lprism32 -xprofile
ONESTEP=yes for all benchmarks in peak and Fortran benchmarks in base

Shell Environments:
 LD_LIBRARY_PATH=/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb
 PRISM_HEAP=268435456
 PRISM_MODE=2

 Stack size set to unlimited via "ulimit -s unlimited"



Kernel Parameters (/etc/system):
 set shmsys:shminfo_shmmin=1
 set shmsys:shminfo_shmmax=1477846784
 set shmsys:shminfo_shmmni=256
 set shmsys:shminfo_shmseg=400

System configuration details located (as of Jun 2002) at
    http://www.sun.com/servers/entry/
```