CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECfp2000 = 551

SPECfp_base2000 = 420

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	540	296	308	519
171.swim	3100	876	354	824	376
172.mgrid	1800	615	293	563	320
173.applu	2100	1035	203	448	469
177.mesa	1400	476	294	307	456
178.galgel	2900	270	1075	197	1469
179.art	2600	84.2	3086	75.3	3453
183.equake	1300	343	379	177	735
187.facerec	1900	308	617	280	679
188.ammp	2200	544	405	405	543
189.lucas	2000	622	322	622	322
191.fma3d	2100	748	281	747	281
200.sixtrack	1100	412	267	299	367
301.apsi	2600	675	385	660	394



Hardware

CPU:	SPARC64 GP
CPU MHz:	788
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	4 to 16/4 to 32/8 to 128
Parallel:	None
Primary Cache:	128KBI+128KBD on chip
Secondary Cache:	8MB(I+D) off chip, per CPU
L3 Cache:	None
Other Cache:	None
Memory:	8192MB
Disk Subsystem:	1 x 18.2GB SCSI (10025rpm)
Other Hardware:	Ethernet

Software

Operating System:	Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler:	Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01. Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01 Sun Performance Library 7
File System:	ufs
System State:	single user

Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
    fdo_pre0=rm -rf ‘pwd‘/*.*.d
    PASS1=-Kpg    PASS2=-Kpu
FDO: (Sun ONE Studio 7)
    fdo_pre0=rm -rf ‘pwd‘/../feedback.profile
    PASS1=-xprofile=collect:‘pwd‘/../feedback
    PASS2=-xprofile=use:‘pwd‘/../feedback
Baseline :
(using Fortran compiler of Sun ONE Studio 7)
-fast -xtarget=ultra3 -lprism32 FDO

(using C compiler of Sun ONE Studio 7)
-fast -xipo=2 -xdepend FDO

Peak:
(using Fortran compiler of Parallelnavi 1.0.2)
 168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=‘pwd‘/../../src
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    -fs -lssl2mtfma FDO ONESTEP=yes
171.swim:  -Kfast_GP=2,GREG,preex,ilfunc,prefetch=3,largepage,commonpad=152,prefetch_iteration=3,unroll=2,nogs,frecipro
     -O4 -fs
172.mgrid: -Kfast_GP=2,preex,GREG,commonpad=144,unroll=3,largepage,prefetch=3
    -O4 -fs
178.galgel: -Kfast_GP=2,GREG,largepage,preex,unroll=3,prefetch_iteration=2,commonpad=24
    -O4 -lssl2mtfma -fs FDO
    RM_SOURCES=lapak.f90
200.sixtrack: -Kfast_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs
301.apsi: -Kfast_GP=2,GREG,preex,ilfunc,largepage,unroll=2 -O4 -fs

(using FORTRAN77 compiler of Sun ONE Studio 7)
173.applu: -fast -xtarget=ultra3 -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
     -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg
     -Qlp=1-av=192-fa=1 -Qoption f90comp -O3 -stackvar ONESTEP=yes

(using FORTRAN90 compiler of Sun ONE Studio 7)
187.facerec: -fast -xarch=v9 FDO ONESTEP=yes
189.lucas: basepeak=1

191.fma3d: -fast -xarch=v8plusb -xcrossfile -stackvar -xdepend
     -xprefetch -Qoption cg -Qlp=1-av=256-t=3-fa=1 FDO ONESTEP=yes

(using C compiler of Sun ONE Studio 7)
177.mesa: -fast -xtarget=ultra2 -xcrossfile -xrestrict -xalias_level=strong
     -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-trace_spec_load=1
     -xarch=v8plus -W2,-Amemopt -xsafe=mem -dn
     FDO ONESTEP=yes
179.art: -fast -xtarget=ultra3 -xipo=2 -xalias_level=strong -xregs=syst -dn
    FDO ONESTEP=yes
183.equake: -fast -xtarget=ultra3 -xalias_level=std -xdepend
    -W2,-whole,-Amemopt:arrayloc,-crit -xprefetch -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -lm
    FDO ONESTEP=yes
188.ammp: -fast -xtarget=ultra3 -xcrossfile -xrestrict
     -xalias_level=strong -xdepend -xprefetch
     -Wc,-Qiselect-funcalign=64 -lprism32 FDO ONESTEP=yes

Portability:
 (for Sun ONE Studio 7)
   178.galgel: -e -fixed
 (for Parallelnavi 1.0.2)
   178.galgel: -Am -Fixed

Note:
 System Tunables: (for /etc/system)
  consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
 shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1
 (for /etc/opt/FJSVpnrm/lpg.conf)
  TSS=512M, SHMSEGSIZE=256M
 Shell Environments:
   LD_LIBRARY_PATH="/usr/lib:/opt/FD7/SUNWspro/lib/v8plusb:/opt/FD7/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"
    LD_LIBRARY_PATH_64="/usr/lib/64:/opt/FD7/SUNWspro/lib/v9:/opt/FD7/SUNWspro/prod/lib/v9"
    PRISM_HEAP=268435456
    PRISM_MODE=2
 Feedback directed optimization was used for all baseline benchmarks and peak benchmarks
 except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 200.sixtrack.
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

System board used with only one CPU present.