CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp server rx2600 (1000 MHz, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 18.7

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jul-2002 | Hardware Avail: Sep-2002 | Software Avail: Oct-2002



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	241	13.5			
175.vpr	2	201	16.2			
176.gcc	2	109	23.4			
181.mcf	2	224	18.6			
186.crafty	2	128	18.1			
197.parser	2	273	15.3			
252.eon	2	130	23.2			
253.perlbmk	2	221	18.9			
254.gap	2	165	15.5			
255.vortex	2	160	27.6			
256.bzip2	2	198	17.6			
300.twolf	2	341	20.4			

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1000
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	no
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	3.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	6GB
Disk Subsystem:	1x36GB SCSI disk
Other Hardware:	N/A

Software

Operating System:	HPUX11i-TCOE B.11.22
Compiler:	HP C/ANSI C Compiler B.11.22
	HP aC++ Compiler B.11.22
	PHSS_27286: C product
	PHSS_27284: C++ product
	PHSS_27285: C++ library
	PHSS_27287: U2comp
	PHSS_27288: Linker
	PHSS_27291: PBO
	PHSS_27293: milli.a
	Caliper v2.1 www.hp.com/go/caliper
File System:	VxFS
System State:	Multi-user

Notes/Tuning Information

```
Portability Flags:
176.gcc     : -DHOST_WORDS_BIG_ENDIAN
181.mcf     : -DWANT_STDC_PROTO
186.crafty  : -DHP
252.eon     : -I. -DFMAX_IS_DOUBLE -DNDEBUG
253.perlbmk : -DSPEC_CPU2000_HP
254.gap     : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
              -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Base Flags:
  all       : +Oprofile=collect/+Oprofile=use
  C         : +Ofaster -exec -Wl,-aarchive_shared
  C++       : +Ofaster +inline_level 2 -minshared
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Kernel Tunables:
  maxdsiz            0x7b03a000
  maxdsiz_64bit   0x04000000000
  maxssiz            0x10000000
  maxssiz_64bit      0x40000000
  vps_ceiling             16384
  vps_pagesize             4096
  swapmem_on                  0
  dbc_max_pct                20
  dbc_min_pct                20

Note:
  EFI shell utility 'cpuconfig' used
  to deconfigure other processors
```