# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## IBM Corporation

IBM eServer pSeries 655 Model 651 (1100 MHz, 1 CPU)

SPECfp2000 = 1103

SPECfp_base2000 = 1037

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Oct-2002 | Hardware Avail: Dec-2002 | Software Avail: Dec-2002

| Benchmark | Reference Time | Base Runtime | Base Ratio | Runtime | Ratio |
|---|---|---|---|---|---|
| 168.wupwise | 1600 | 109 | 1470 | 109 | 1472 |
| 171.swim | 3100 | 183 | 1697 | 183 | 1695 |
| 172.mgrid | 1800 | 264 | 682 | 225 | 798 |
| 173.applu | 2100 | 227 | 927 | 206 | 1017 |
| 177.mesa | 1400 | 251 | 557 | 212 | 660 |
| 178.galgel | 2900 | 126 | 2309 | 98.5 | 2944 |
| 179.art | 2600 | 170 | 1534 | 168 | 1548 |
| 183.equake | 1300 | 78.4 | 1659 | 78.4 | 1659 |
| 187.facerec | 1900 | 151 | 1258 | 147 | 1294 |
| 188.ammp | 2200 | 332 | 662 | 332 | 662 |
| 189.lucas | 2000 | 169 | 1181 | 155 | 1293 |
| 191.fma3d | 2100 | 260 | 808 | 250 | 840 |
| 200.sixtrack | 1100 | 238 | 462 | 231 | 477 |
| 301.apsi | 2600 | 297 | 875 | 297 | 877 |




### Hardware

| | |
|---|---|
| CPU: | POWER4 |
| CPU MHz: | 1100 |
| FPU: | Integrated |
| CPU(s) enabled: | 1 core, 4 chips, 2 cores/chip, 4 chips/MCM |
| CPU(s) orderable: | 1 MCM (order by # MCM) |
| Parallel: | No |
| Primary Cache: | 64KBI+32KBD (on chip) per core |
| Secondary Cache: | 1440KB unified (off chip) per chip |
| L3 Cache: | 128MB unified (off-chip) per MCM, 1 MCM in SUT (4 chips per MCM) |
| Other Cache: | None |
| Memory: | 16 GB |
| Disk Subsystem: | 1x18.2 GB SCSI |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | AIX 5L V5.1 |
| Compiler: | IBM C for AIX, Version 6.0<br>IBM XL FORTRAN for AIX, Version 8.1.0.1<br>Other Software: ESSL 3.3, MASS 3.0 |
| File System: | AIX/JFS |
| System State: | Multi-User |

## Notes/Tuning Information

```
Portability Flags
  -qfixed used in: wupwise, swim, mgrid, applu, galgel,
   sixtrack, apsi
  -qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:
  C:
  -O5 -qalign=natural -blpdata -lmass
  Fortran:
  -O5 -qalign=natural -blpdata -lmass

Floating Point Peak Flags
168.wupwise
  -O5 -qipa=partition=large
171.swim
  -O4 -q64 -blpdata
172.mgrid
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
    -O5 -qarch=pwr3 -qtune=pwr3 -blpdata
  173.applu
    -O3 -qarch=pwr3 -qtune=pwr3 -lmass -qhot -blpdata
  177.mesa
    -qpdf1/pdf2
    fdpr -v -R3
    -O3 -qarch=pwr3 -qtune=pwr3 -qipa=level=2 -qalign=natural -blpdata
  178.galgel
    -qpdf1/pdf2
    fdpr -v -R3
    -O5 -qalign=natural -qessl -lessl -lmass -blpdata
  179.art
   -O4 -lhmu
  183.equake
    BASEPEAK = 1
  187.facerec
    fdpr -v -R3
    -O5 -lmass -blpdata
  188.ammp
    BASEPEAK = 1
  189.lucas
    -O3 -q64 -blpdata
  191.fma3d
    -qpdf1/pdf2
    -O5 -qarch=pwr4 -qtune=pwr3 -lhmu -qalign=natural -blpdata
  200.sixtrack
    -qpdf1/pdf2
    -O5 -lmass
  301.apsi
    -O5 -qarch=pwr4 -qtune=pwr3 -blpdata

    MCM: Acronym for "Multi-Chip Module"
    SUT: Acronym for "System Under Test"

    7 processors were deconfigured through the configuration menu.

    fpdr: Feedback directed program restructuring tool
    /usr/spec2000 filesystem mounted with no JFS log file I/O.
    APAR IY 35692 was applied to AIX to enable new hardware support.
    ulimits set to unlimited.
    C: IBM VAC++ invoked as xlc
    Fortran 77 and 90: IBM XL Fortran for AIX invoked as xlf90.
    Large page mode and memory affinity were set as follows:
      vmtune64 -g 16777216 -L 32 -y1
      chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
      bosboot -a
      shutdown -r
```