



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer ES80 7/1000

SPECint_rate2000 = 68.9
SPECint_rate_base2000 = 62.4

SPEC license #: 2 | Tested by: HP | Test date: Dec-2002 | Hardware Avail: Jan-2003 | Software Avail: Jan-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	283	45.9	8	282	46.0
175.vpr	8	198	65.7	8	193	67.3
176.gcc	8	157	65.0	8	140	72.8
181.mcf	8	296	56.4	8	185	90.1
186.crafty	8	119	78.2	8	119	78.2
197.parser	8	408	41.0	8	321	52.0
252.eon	8	161	75.2	8	162	74.4
253.perlbnk	8	285	58.6	8	271	61.6
254.gap	8	201	50.7	8	178	57.2
255.vortex	8	206	85.7	8	188	93.8
256.bzip2	8	216	64.4	8	205	68.1
300.twolf	8	346	80.5	8	339	82.0

Hardware

CPU: Alpha 21364
CPU MHz: 1000
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2 to 8
Parallel: No
Primary Cache: 64KB(I)+64KB(D) on chip
Secondary Cache: 1.75MB on chip per CPU
L3 Cache: None
Other Cache: None
Memory: 32GB
Disk Subsystem: 36GB SCSI
Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1B (Rev. 2650)
+IPK
Compiler: Compaq C V6.5-011-48C5K
Program Analysis Tools V2.0
Spike V5.2 (506A)
Compaq C++ V6.5-028
File System: ufs
System State: Multi-user

Notes/Tuning Information

Baseline C : cc -arch ev7 -fast +CFB ONESTEP
C++: cxx -arch ev7 -O2 ONESTEP

Peak:

The following use: -g3 -arch ev7 ONESTEP
175.vpr 181.mcf 197.parser 253.perlbnk

The following use: -g3 -arch ev6 ONESTEP
164.gzip 176.gcc 254.gap 255.vortex 256.bzip2 300.twolf

Individual benchmark tuning:

164.gzip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume_restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
252.eon: -arch ev7 -O2 -all -ldensemalloc -none
253.perlbnk: -fast -non_shared +CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer ES80 7/1000

SPECint_rate2000 = 68.9
SPECint_rate_base2000 = 62.4

SPEC license #: 2 | Tested by: HP | Test date: Dec-2002 | Hardware Avail: Jan-2003 | Software Avail: Jan-2003

Notes/Tuning Information (Continued)

```
254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
256.bzip2: -fast -O4 -non_shared +CFB
300.twolf: -fast -O4
          -ldensemalloc -non_shared +CFB +IFB
```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

```
Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbnk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
     -DSPEC_CPU2000_LP64
```

Information on UNIX V5.1B Patches can be found at
<http://ftpl.service.digital.com/public/unix/v5.1b/>



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer ES80 7/1000

SPECint_rate2000 = 68.9
SPECint_rate_base2000 = 62.4

SPEC license #: 2 | Tested by: HP | Test date: Dec-2002 | Hardware Avail: Jan-2003 | Software Avail: Jan-2003

Notes/Tuning Information (Continued)

vm:

```
vm_bigpg_enabled = 1  
vm_bigpg_thresh=16  
vm_swap_eager = 0
```

proc:

```
max_per_proc_address_space = 0x40000000000  
max_per_proc_data_size = 0x40000000000  
max_per_proc_stack_size = 0x40000000000  
max_proc_per_user = 2048  
max_threads_per_user = 0  
maxusers = 16384  
per_proc_address_space = 0x40000000000  
per_proc_data_size = 0x40000000000  
per_proc_stack_size = 0x40000000000
```