



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 2000 (1.2GHz)

SPECfp2000 = 1118

SPECfp_base2000 = 953

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	179	894	167	959
171.swim	3100	299	1037	117	2659
172.mgrid	1800	255	706	255	706
173.applu	2100	282	746	220	956
177.mesa	1400	201	698	191	735
178.galgel	2900	146	1992	122	2374
179.art	2600	26.0	10006	23.5	11077
183.earth	1300	83.5	1556	80.4	1616
187.facerec	1900	161	1178	161	1179
188.amp	2200	367	599	338	651
189.lucas	2000	378	530	279	716
191.fma3d	2100	431	487	384	547
200.sixtrack	1100	270	408	242	454
301.apsi	2600	402	647	401	648

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-2
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 2GB 4-way interleaved
Disk Subsystem: 1 x 73GB 10K RPM FC-AL Disk, Sun Option X6805A
Other Hardware: None

Software

Operating System: Solaris 9 12/02
Compiler: Sun ONE Studio 8 (pre-FCS build 3/09)
Sun Performance Library 8 (pre-FCS build 3/09)
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 2000 (1.2GHz)

SPECfp2000 = 1118
SPECfp_base2000 = 953

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Notes/Tuning Information (Continued)

```

172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
          -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ammp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

System Settings:

2nd cpu physically removed from system