



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D850EMVR motherboard (3.06 GHz, Pentium 4 processor with Hyper-Threading Technology)

SPECint2000 = 1098

SPECint\_base2000 = 1088

SPEC license #: 13 Tested by: Intel Corporation Test date: Jan-2003 Hardware Avail: Nov-2002 Software Avail: Nov-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	117	1193	117	1196	
175.vpr	1400	205	683	218	643	
176.gcc	1100	88.1	1249	88.0	1251	
181.mcf	1800	234	768	234	770	
186.crafty	1000	88.6	1129	87.7	1140	
197.parser	1800	171	1051	171	1052	
252.eon	1300	95.9	1355	82.5	1576	
253.perlbmk	1800	137	1317	137	1319	
254.gap	1100	75.8	1452	75.6	1454	
255.vortex	1900	111	1715	111	1715	
256.bzip2	1500	174	862	174	863	
300.twolf	3000	387	775	387	776	

### Hardware

CPU: Intel Pentium 4 Processor with Hyper-Threading Technology(3.06 GHz, 533 MHz bus)  
CPU MHz: 3067  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12k micro-ops I + 8KBD on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 512 MB (2 256 MB PC1066-32 RDRAM non-ECC modules)  
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100  
Other Hardware: None

### Software

Operating System: Windows XP Professional(Build 2600) SP1  
Compiler: Intel C++ Compiler 7.0 Build 021018Z  
Microsoft Visual Studio .Net 7.0.9466(for libraries)  
File System: FAT32  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO
Base tuning for C++ programs: -QxW -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxW -Qipo -Oa -O3 +FDO
175.vpr: -QxW -Qwp_ipo -O3 +FDO
176.gcc: -QxW -Qipo -O3 +FDO
181.mcf: -QxW -Qipo -O3 +FDO
186.crafty: -QxW -Qipo -Oa -O3 +FDO
197.parser: -QxW -Qipo -O3 +FDO
252.eon: -QxW -Qipo -O3 +FDO
253.perlbmk: -QxW -Qipo -O3 +FDO
254.gap: -QxW -Qipo -O3 +FDO
255.vortex: basepeak=yes
256.bzip2: -QxW -Qipo -Oa -O3 +FDO
```



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Intel Corporation**

Intel D850EMVR motherboard (3.06 GHz, Pentium 4 processor with Hyper-Threading Technology)

SPECint2000 = 1098

SPECint\_base2000 = 1088

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jan-2003 | Hardware Avail: Nov-2002 | Software Avail: Nov-2002

## Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz