CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM IntelliStation POWER 275 Workstation (1000 MHz, 1 CPU)

SPECint2000 = 683

SPECint_base2000 = 617

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	304	460	304	460
175.vpr	1400	233	600	233	600
176.gcc	1100	163	676	163	676
181.mcf	1800	180	1003	170	1056
186.crafty	1000	187	534	151	664
197.parser	1800	680	265	317	567
252.eon	1300	164	792	164	792
253.perlbmk	1800	374	482	332	542
254.gap	1100	194	567	194	567
255.vortex	1900	197	962	192	992
256.bzip2	1500	226	664	220	683
300.twolf	3000	361	831	358	839



Hardware

CPU:	POWER4+
CPU MHz:	1000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip, 1 processor chip/DCM
CPU(s) orderable:	1 (order by # cores)
Parallel:	No
Primary Cache:	64KBI+32KBD (on chip)
Secondary Cache:	1536KB unified (on chip)
L3 Cache:	8MB unified (off-chip) per DCM, 1 DCM in SUT
Other Cache:	None
Memory:	8 GB
Disk Subsystem:	1x36GB SCSI, 10K RPM
Other Hardware:	None

Software

Operating System:	AIX 5L V5.2
Compiler:	IBM C for AIX, Version 6.0 IBM VisualAge C++ Professional for AIX, Version 6.0
File System:	AIX/JFS
System State:	Multi-User

Notes/Tuning Information

```
Integer Portability Flags:
  176.gcc:     -ma -DHOST_WORDS_BIG_ENDIAN
  186.crafty:  -DAIX
  252.eon:     srcalt=fmax_errno
               -I. -DNDEBUG
  253.perlbmk: -DSPEC_CPU2000_AIX
  254.gap:     -DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO
               -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
  300.twolf:   -DHAVE_SIGNED_CHAR

Base Optimization Flags:
  C:
  -qpdf1/pdf2
  -O5 -blpdata -qalign=natural
  C++:
  -qpdf1/pdf2
  -O5 -lhmu -qalign=natural

Integer Peak Optimization Flags
164.gzip
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    BASEPEAK = 1
    "CC      = /usr/vac/bin/xlc"
  175.vpr
    BASEPEAK = 1
  176.gcc
    BASEPEAK = 1
  181.mcf
    fdpr -v -R3
    -O5 -blpdata -D_ILS_MACROS
  186.crafty
    -qpdf1/pdf2
    fdpr -v -R3
    -O3 -q64
  197.parser
    -O5 -blpdata -D_ILS_MACROS
  252.eon
    BASEPEAK = 1
  253.perlbmk
    -qpdf1/pdf2
    -O5 -lhmu -qalign=natural
  254.gap
    BASEPEAK = 1
  255.vortex
    -qpdf1/pdf2
    -O5 -lhmu -qalign=natural
  256.bzip2
    -qpdf1/pdf2
    -O5 -blpdata -qarch=pwr3 -qtune=pwr3
  300.twolf
    -qpdf1/pdf2
    -O5 -lhmu -qalign=natural -blpdata
    "CC      = /usr/vac/bin/xlc"

     Approved alternate-source file 252.eon.fmax_errno.src.alt.tar.gz
     was used with 252.eon for POSIX-compatibility.

     DCM: Acronym for "Dual-Chip Module"
     SUT: Acronym for "System Under Test"

     fpdr: Feedback directed program restructuring tool
     /usr/spec2000 filesystem mounted with no JFS log file I/O.
     APAR IY 43549 was applied to AIX to enable new hardware support.
     ulimits set to unlimited.
     C: IBM VAC++ invoked as cc except where noted as xlc
     C++: IBM VAC++ invoked as xlC
     Large page mode and memory affinity were set as follows:
       vmo -r -o lgpg_regions=400 -o lgpg_size=16777216 -o memory_affinity=1
       chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
       shutdown -r
       export MEMORY_AFFINITY=MCM
```