



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM IntelliStation POWER 275 Workstation (1450 MHz, 2 CPU)

SPECfp_rate2000 = 19.9

SPECfp_rate_base2000 = 19.6

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	130	28.4	2	132	28.0
171.swim	2	344	20.9	2	343	21.0
172.mgrid	2	264	15.8	2	261	16.0
173.applu	2	366	13.3	2	360	13.5
177.mesa	2	205	15.9	2	164	19.8
178.galgel	2	121	55.5	2	111	60.4
179.art	2	268	22.5	2	284	21.2
183.equake	2	152	19.8	2	152	19.8
187.facerec	2	190	23.2	2	192	23.0
188.amp	2	319	16.0	2	319	16.0
189.lucas	2	278	16.7	2	278	16.7
191.fma3d	2	298	16.4	2	310	15.7
200.sixtrack	2	182	14.0	2	185	13.8
301.apsi	2	334	18.1	2	327	18.4

Hardware

CPU: POWER4+
 CPU MHz: 1450
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 1 processor chip/DCM
 CPU(s) orderable: 1,2 (order by # cores)
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip) per core
 Secondary Cache: 1536KB unified (on chip) per chip
 L3 Cache: 8MB unified (off-chip) per DCM, 1 DCM in SUT
 Other Cache: None
 Memory: 8 GB
 Disk Subsystem: 1x36GB SCSI, 10K RPM
 Other Hardware: None

Software

Operating System: AIX 5L V5.2
 Compiler: IBM C for AIX, Version 6.0
 IBM XL FORTRAN for AIX, Version 8.1.1.0
 Other Software: ESSL 3.3.0.5, MASS 3.0
 File System: AIX/JFS
 System State: Multi-User

Notes/Tuning Information

Portability Flags

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu, 178.galgel, 200.sixtrack, 301.apsi
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

Base Optimization Flags:

C:
 -O5 -qalign=natural -blpdata -lmass
 Fortran:
 -O5 -qalign=natural -blpdata -lmass

Floating Point Peak Flags

168.wupwise
 -O5 -qipa=partition=large
 171.swim
 -O4 -q64 -blpdata
 172.mgrid



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM IntelliStation POWER 275 Workstation (1450 MHz, 2 CPU)

SPECfp_rate2000 = 19.9

SPECfp_rate_base2000 = 19.6

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

Notes/Tuning Information (Continued)

```

-05 -qarch=pwr3 -qtune=pwr3 -blpdata
173.applu
-03 -qarch=pwr3 -qtune=pwr3 -lmass -qhot -blpdata
177.mesa
-qpdf1/pdf2
fdpr -v -R3
-03 -qarch=pwr3 -qtune=pwr3 -qipa=level=2 -qalign=natural -blpdata
178.galgel
-qpdf1/pdf2
fdpr -v -R3
-05 -qalign=natural -qessl -lessl -lmass -blpdata
179.art
-04 -lhmu
183.quake
BASEPEAK = 1
187.facerec
fdpr -v -R3
-05 -lmass -blpdata
188.amp
BASEPEAK = 1
189.lucas
-03 -q64 -blpdata
191.fma3d
-qpdf1/pdf2
-05 -qarch=pwr4 -qtune=pwr3 -lhmu -qalign=natural -blpdata
200.sixtrack
-qpdf1/pdf2
-05 -lmass
301.apsi
-05 -qarch=pwr4 -qtune=pwr3 -blpdata

```

DCM: Acronym for "Dual-Chip Module"
SUT: Acronym for "System Under Test"

fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O.
APAR IY 43549 was applied to AIX to enable new hardware support.
ulimits set to unlimited.
C: IBM VAC++ invoked as xlc
Fortran 77 and 90: IBM XL Fortran for AIX invoked as xlf90.
Large page mode and memory affinity were set as follows:
vmo -r -o lpgg_regions=400 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE \$USER
shutdown -r
export MEMORY_AFFINITY=MCM