CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480 (1050MHz)

SPECfp2000 = 962

SPECfp_base2000 = 826

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	206	777	194	825
171.swim	3100	327	949	133	2334
172.mgrid	1800	288	625	288	624
173.applu	2100	327	643	251	835
177.mesa	1400	231	607	221	633
178.galgel	2900	168	1725	140	2077
179.art	2600	29.7	8760	26.9	9652
183.equake	1300	96.8	1342	93.3	1393
187.facerec	1900	183	1038	183	1039
188.ammp	2200	429	512	399	552
189.lucas	2000	422	474	327	611
191.fma3d	2100	499	421	441	476
200.sixtrack	1100	353	311	321	343
301.apsi	2600	457	570	457	570



Hardware

CPU:	UltraSPARC III Cu
CPU MHz:	1050
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	2,4
Parallel:	No
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	8MB(I+D) off chip
L3 Cache:	None
Other Cache:	None
Memory:	4GB 4-way interleaved
Disk Subsystem:	2 x 36GB Seagate ST336605
Other Hardware:	None

Software

Operating System:	Solaris 9
Compiler:	Sun ONE Studio 8 Sun Performance Library 8
File System:	ufs with ufs logging
System State:	Multi-User

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  CXX: CC
  F90: f90
  F77: f90

Floating point base flags:
    C:  -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
  F90:  -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:
 ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

 168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
 171.swim:    -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
              -Qoption iropt -Atile:skewp,-Ainline:cs=700
              (no feedback)
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 172.mgrid:   -fast -xipo=2
 173.applu:   -fast -xipo=2
              -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
              -Qoption iropt -Aujam:inner=g
 177.mesa:    -fast -xipo=2 -xalias_level=strong -xrestrict
              -Wc,-Qms_pipe+unoovf
 178.galgel:  -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
              RM_SOURCES=lapak.f90
 179.art:     -fast -xipo=2 -xalias_level=std
              -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
 183.equake:  -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
 187.facerec: -fast -xipo=2
 188.ammp:    -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
 189.lucas:   -fast -xipo=2 -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
              -Qoption f90comp -array_pad_rows,1977
 191.fma3d:   -fast -xipo=2 -stackvar -xprefetch_level=3
              -Qoption iropt -Apf:pdl=1
 200.sixtrack:-O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
 301.apsi:    -fast -xipo=2

Feedback is done as follows, unless otherwise noted:
 fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
 PASS1:     -xprofile=collect:./feedback
 PASS2:     -xprofile=use:./feedback

Portability:
 178.galgel:  -e -fixed

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"
  MPSSHEAP=512K
  MPSSSTACK=512K
  LD_PRELOAD=mpss.so.1

Kernel Parameters (/etc/system):
set cpu_bringup_set=4
set autoup=900
set tune_t_fsflushr=1
System Settings:
2nd CPU disabled at boot time by using /etc/system
parameter "cpu_bringup_set" to bring up only cpu#2
```