



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel D875PBZ (AA-206) motherboard

SPECint2000 = 1620
SPECint_base2000 = 1583

SPEC license #: 13 Tested by: Intel Corporation Test date: Sep-2003 Hardware Avail: Nov-2003 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	104	1341	104	1341	
175.vpr	1400	117	1197	117	1197	
176.gcc	1100	57.0	1931	57.0	1931	
181.mcf	1800	106	1691	106	1690	
186.crafty	1000	79.7	1255	79.7	1254	
197.parser	1800	128	1407	128	1407	
252.eon	1300	77.3	1683	67.9	1915	
253.perlbmk	1800	122	1478	110	1634	
254.gap	1100	62.9	1750	62.9	1750	
255.vortex	1900	69.0	2752	69.0	2752	
256.bzip2	1500	112	1334	108	1391	
300.twolf	3000	178	1681	178	1689	

Hardware

CPU: Intel Pentium 4 Processor with Hyper-Threading Technology Extreme Edition (3.2 GHz, 800 MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 2MB(I+D) on chip
Other Cache: N/A
Memory: 512 MB (4 128 MB PC3200 Samsung CL3-3-3)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional Service Pack 1a
Compiler: Intel C++ Compiler 8.0
Microsoft Visual Studio .Net 7.0(for libraries)
MicroQuill SmartHeap library V6.0
File System: FAT32
System State: Default

Notes/Tuning Information

ONESTEP=yes +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxN -Qipo -O3 +FDO
Base tuning for C++ programs: -QxN -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxN -Qipo -Oa -O3 +FDO
175.vpr: -QxN -Qipo -O3 +FDO
176.gcc: -QxN -Qipo -O3 +FDO
181.mcf: -QxN -Qipo -O3 +FDO
186.crafty: -QxN -Qipo -Oa -O3 +FDO
197.parser: -QxN -Qipo -O3 +FDO
252.eon: -QxN -Qipo -O3 +FDO
253.perlbmk: -QxN -Qipo -O3 +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -Qipo -Oa -Qunroll1 +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel D875PBZ (AA-206) motherboard

SPECint2000 =	1620
SPECint_base2000 =	1583

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Sep-2003 | Hardware Avail: Nov-2003 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

300.twolf: -QxN -Qipo -O3 +FDO shlw32M.lib
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1
Product description located as of 9/2003:
<http://developer.intel.com/design/motherbd/bz/index.htm>
Motherboard is available through Intel OEM Distribution Channel. See
http://www.intel.com/cd/channel/reseller/asm-na/eng/products/box_desktop_boards/p4_boards/p4_dsk_board_d875pbz/index.htm
The system bus runs at 800 MHz
shlw32M.lib is the SmartHeap library V6.0 from <http://www.microquill.com/smartheap/index.html>