CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 350 (1400MHz/1.5MB, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 44.4

SPEC license #: 4 | Tested by: SGI | Test date: Dec-2003 | Hardware Avail: Jan-2004 | Software Avail: Dec-2003



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	162	40.1			
175.vpr	4	199	32.7			
176.gcc	4	106	48.0			
181.mcf	4	250	33.4			
186.crafty	4	90.2	51.5			
197.parser	4	249	33.6			
252.eon	4	91.9	65.6			
253.perlbmk	4	171	49.0			
254.gap	4	142	36.0			
255.vortex	4	122	72.1			
256.bzip2	4	185	37.7			
300.twolf	4	270	51.6			

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1400
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	2-16
Parallel:	No
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	1.5MB (on chip) per CPU
Other Cache:	N/A
Memory:	8 GB (8*512MB PC2700 DIMMS per 2cpu module)
Disk Subsystem:	1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware:	None

Software

Operating System:	SGI ProPack(TM) v2.3
Compiler:	Intel(R) C++ Compiler for Linux 8.0 (Build 20031017) MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System:	xfs
System State:	Single-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen  PASS2=-prof_use

Baseline optimization flags:
  C programs:       -fast -auto_ilp32 +FDO
  C++ programs:     -fast -ansi_alias +FDO
  Extra Libraries:  libsmartheap64.a

Portability Flags:
  176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
  186.crafty: -DLINUX_i386
  252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
  253.perlbmk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
  254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
           -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
  255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.
```