CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1300MHz, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 367

SPEC license #: 4 | Tested by: SGI | Test date: Dec-2003 | Hardware Avail: Jun-2003 | Software Avail: Dec-2003



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	183	284			
175.vpr	32	170	306			
176.gcc	32	104	394			
181.mcf	32	178	375			
186.crafty	32	96.7	384			
197.parser	32	236	283			
252.eon	32	99.4	485			
253.perlbmk	32	179	373			
254.gap	32	150	272			
255.vortex	32	120	588			
256.bzip2	32	162	343			
300.twolf	32	256	435			

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1300
FPU:	Integrated
CPU(s) enabled:	32 cores, 32 chips, 1 core/chip
CPU(s) orderable:	4-64
Parallel:	No
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	3.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	64 GB (16*512MB PC2700 DIMMS per 4cpu module)
Disk Subsystem:	1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware:	None

Software

Operating System:	SGI ProPack(TM) v2.3
Compiler:	Intel(R) C++ Compiler for Linux 8.0 (Build 20031017) MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System:	xfs
System State:	Single-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen  PASS2=-prof_use

Baseline optimization flags:
  C programs:       -fast -auto_ilp32 +FDO
  C++ programs:     -fast -ansi_alias +FDO
  Extra Libraries:  libsmartheap64.a

Portability Flags:
  176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
  186.crafty: -DLINUX_i386
  252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
  253.perlbmk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
  254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
           -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
  255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.
```