CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity Server rx4640 (1300 MHz, Itanium 2)

SPECfp_rate2000 = 37.9

SPECfp_rate_base2000 = 37.9

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Jan-2004 | Software Avail: Jan-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	136	27.3	2	136	27.3
171.swim	2	145	49.6	2	145	49.6
172.mgrid	2	129	32.3	2	129	32.3
173.applu	2	73.1	66.6	2	73.1	66.6
177.mesa	2	132	24.6	2	132	24.6
178.galgel	2	80.4	83.7	2	80.4	83.7
179.art	2	48.1	125	2	48.1	125
183.equake	2	67.2	44.9	2	67.2	44.9
187.facerec	2	126	35.0	2	126	35.0
188.ammp	2	183	28.0	2	183	28.0
189.lucas	2	156	29.8	2	156	29.8
191.fma3d	2	218	22.4	2	218	22.4
200.sixtrack	2	90.7	28.1	2	90.7	28.1
301.apsi	2	301	20.0	2	301	20.0

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1300
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	no
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	3.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	32GB (16 * 2GB DIMMs)
Disk Subsystem:	1x36GB 10k RPM SCSI disk
Other Hardware:	N/A

Software

Operating System:	Red Hat Linux Advanced Server release 2.1AS (Update 2)
Compiler:	Intel C++ Compiler 8.0 for Linux, Build 20031017 Intel Fortan Compiler 8.0 for Linux, Build 20031017
File System:	ext3
System State:	Multi-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen  PASS2=-prof_use
Base tuning flags:
         C programs: -O3 -ipo +FDO -ansi_alias
   Fortran programs: -O3 -ipo +FDO
Portability:
         178.galgel: -FI

Peak flags same as baseline (basepeak=true set globally)


Note:
  'ELILO boot: linux maxcpus=0' used to
  deconfigure other processors if necessary
  Kernel was built with the configuration of 64K page size.
```