CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity Server rx4640 (1500 MHz, Itanium 2)

SPECfp_rate2000 = 25.1

SPECfp_rate_base2000 = 25.1

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Jan-2004 | Software Avail: Jan-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	114	16.2	1	114	16.2
171.swim	1	73.4	49.0	1	73.4	49.0
172.mgrid	1	71.4	29.2	1	71.4	29.2
173.applu	1	60.3	40.4	1	60.3	40.4
177.mesa	1	116	14.0	1	116	14.0
178.galgel	1	63.4	53.0	1	63.4	53.0
179.art	1	38.8	77.7	1	38.8	77.7
183.equake	1	46.4	32.5	1	46.4	32.5
187.facerec	1	94.9	23.2	1	94.9	23.2
188.ammp	1	149	17.1	1	149	17.1
189.lucas	1	109	21.3	1	109	21.3
191.fma3d	1	181	13.5	1	181	13.5
200.sixtrack	1	78.2	16.3	1	78.2	16.3
301.apsi	1	257	11.7	1	257	11.7

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1500
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	no
Primary Cache:	16KBI + 16KBD (on chip) per CPU
Secondary Cache:	256KB (on chip) per CPU
L3 Cache:	6.0MB (on chip) per CPU
Other Cache:	N/A
Memory:	32GB (16 * 2GB DIMMs)
Disk Subsystem:	1x36GB 10k RPM SCSI disk
Other Hardware:	N/A

Software

Operating System:	Red Hat Linux Advanced Server release 2.1AS (Update 2)
Compiler:	Intel C++ Compiler 8.0 for Linux, Build 20031017 Intel Fortan Compiler 8.0 for Linux, Build 20031017
File System:	ext3
System State:	Multi-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen  PASS2=-prof_use
Base tuning flags:
         C programs: -O3 -ipo +FDO -ansi_alias
   Fortran programs: -O3 -ipo +FDO
Portability:
         178.galgel: -FI

Peak flags same as baseline (basepeak=true set globally)


Note:
  'ELILO boot: linux maxcpus=0' used to
  deconfigure other processors if necessary
  Kernel was built with the configuration of 64K page size.
```