CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D875PBZ motherboard (AA-206) (3.4 GHz, Pentium 4 Processor with Hyper-Threading Technology Extreme Edition)

SPECfp2000 = 1556

SPECfp_base2000 = 1544

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	89.3	1791	89.4	1789
171.swim	3100	145	2143	145	2143
172.mgrid	1800	140	1286	140	1286
173.applu	2100	158	1331	152	1379
177.mesa	1400	94.2	1486	94.1	1488
178.galgel	2900	95.5	3038	95.4	3041
179.art	2600	113	2302	105	2474
183.equake	1300	83.5	1557	84.6	1536
187.facerec	1900	102	1858	102	1858
188.ammp	2200	168	1310	167	1319
189.lucas	2000	120	1665	120	1666
191.fma3d	2100	162	1294	162	1294
200.sixtrack	1100	166	665	164	671
301.apsi	2600	221	1177	221	1176



Hardware

CPU:	Intel Pentium 4 Processor with Hyper-Threading Technology Extreme Edition (3.4 GHz, 800 MHz bus)
CPU MHz:	3400
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 8KBD on chip
Secondary Cache:	512KB(I+D) on chip
L3 Cache:	2MB (I+D) on chip
Other Cache:	N/A
Memory:	1 GB(2 512MB PC3200 Samsung Double-sided CL3-3-3 DIMMs)
Disk Subsystem:	Seagate ST3160023AS 160 GB Serial ATA (7200 RPM, 8MB cache)
Other Hardware:	None

Software

Operating System:	Windows XP Professional Service Pack 1a
Compiler:	Intel C++ and Fortran Compiler 8.0 Build 20031017Z Microsoft Visual Studio .Net 7.0(for libraries) MicroQuill SmartHeap library V6.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning:  -QxN -fast -Qansi_alias +FDO
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -QxN -fast -Qansi_alias +FDO
171.swim:     -QxN -fast -Qansi_alias +FDO
172.mgrid:    -QxN -fast -Qansi_alias +FDO
173.applu:    -QxN -fast -Qscalar_rep- -Qauto  +FDO
177.mesa:     -QxN -fast -Oa -Qscalar_rep- +FDO
178.galgel:   -QxN -fast -Qansi_alias +FDO
179.art:      -Oa -Qipo -Qunroll4 -Zp4
183.equake:   -QxN -Oa -Qrcd -Qipo +FDO
187.facerec:  -QxN -fast -Qunroll1 -Qscalar_rep- +FDO
188.ammp:     -Oa -QxN
189.lucas:    -QxN -fast -Qprefetch- +FDO
191.fma3d:    basepeak=yes
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxN +FDO
301.apsi: -QxN -fast +FDO
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1
Product description located as of 9/2003:
http://developer.intel.com/design/motherbd/bz/index.htm
Motherboard is available through Intel OEM Distribution Channel. See
http://www.intel.com/cd/channel/reseller/asmo-na/eng/products/box_desktop_boards/p4_boards/p4_dsk_board_d875pbz/index.htm
The system bus runs at 800 MHz
shlW32M.lib is the SmartHeap library V6.0 from http://www.microquill.com/smartheap/index.html
An AGP video card is installed