



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (1890MHz)

SPECfp_rate2000 = 252
SPECfp_rate_base2000 = 184

SPEC license #: 19 Tested by: Fujitsu Limited Test date: May-2004 Hardware Avail: Sep-2004 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	202	147	16	136	219
171.swim	16	543	106	16	109	529
172.mgrid	16	351	95.3	16	332	101
173.applu	16	445	87.5	16	142	275
177.mesa	16	148	175	16	131	198
178.galgel	16	109	492	16	93.9	573
179.art	16	16.3	2968	16	15.8	3055
183.quake	16	121	199	16	121	199
187.facerec	16	201	176	16	141	249
188.amp	16	196	209	16	186	220
189.lucas	16	383	96.8	16	330	113
191.fma3d	16	303	129	16	303	129
200.sixtrack	16	200	102	16	188	109
301.apsi	16	282	171	16	222	217

Hardware

CPU: SPARC64 V
CPU MHz: 1890
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 1 to 16 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 3MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 32768MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 9 4/04
Compiler: Fujitsu Parallelnavi 2.3 with patch 913221-03
Sun Studio 8
Sun Performance Library 8
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.3)
fdo_pre0=rm -rf `pwd`/*.f.d
PASS1=-Kpg
PASS2=-Kpu
FDO: (for Sun Studio 8)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Floating point base flags:
(using Fortran compiler of Parallelnavi 2.3)
-Kfast_GP2=3,prefetch_infer,GREG_SYSTEM -O5
(using C compiler of Sun Studio 8)
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO
```

Floating point peak flags:



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (1890MHz)

SPECfp_rate2000 = 252
SPECfp_rate_base2000 = 184

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2004 | Hardware Avail: Sep-2004 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

(using Fortran compiler of Parallelnavi 2.3)

172.mgrid: -Kfast_GP2=2,GREG_SYSTEM -O4 -Kcommonpad=180,alignc=64
178.galgel: -Kfast_GP2=2,GREG_SYSTEM,prefetch_infer,frecipro,
commonpad=152,arraypad_const=11,alignl=64 -x dir=./ -O4 FDO
189.lucas: -Kfast_GP2=3 -O5 -x dir=./ -Kunroll=2 FDO
191.fma3d: basepeak=yes
200.sixtrack: -Kfast_GP2=3 -O4 -x dir=./ -Kunroll=3 -fs FDO

(using Fortran compiler of Sun Studio 8)

168.wupwise: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xarch=v8plusa -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
ONESTEP=yes FDO
171.swim: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xpad=common:1660 -xprefetch=latx:2.6
-Qoption cg -Qiselect-funcalign=64
-Qoption iropt -Ainline:cs=700,Atile:skewp:b10
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xprefetch=latx:1.6
-Qoption cg -Qlp=1-av=192-t=4-fa=1-fl=0,-Qms_pipe+prefolim=7
-Qoption iropt -Aujam:inner=g ONESTEP=yes FDO
187.facerec: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xarch=v8plus -xprefetch=latx:1.6 ONESTEP=yes FDO
301.apsi: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 ONESTEP=yes FDO

(using C compiler of Sun Studio 8)

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xchip=ultra -xalias_level=strong -xipo=2 -xrestrict
-Wc,-Qgsched-T4,-Qgsched-trace_late=1,-Qiselect-funcalign=64,
-Qms_pipe+unoovf ONESTEP=yes FDO
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=std -xarch=v8plusa -xipo=2 -xprefetch=latx:1.2
-Wc,-Qiselect-funcalign=64 ONESTEP=yes FDO
183.equake: basepeak=yes
188.ammp: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=std -xipo=2 -xprefetch=latx:1.2 -xrestrict
-Wc,-Qiselect-funcalign=64 ONESTEP=yes FDO

Portability:

178.galgel(base&peak): -Am -Fixed
187.facerec(base): -Am
191.fma3d(base): -Am

System Tunables:

(for /etc/system)
set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400
set memscrub_period_sec=172800

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (1890MHz)

SPECfp_rate2000 = 252
SPECfp_rate_base2000 = 184

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2004 | Hardware Avail: Sep-2004 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

Processes were bound to CPUs using "submit=pbind".

Extended Interleave Mode enabled.

Sun Studio 8, posted at URL <http://www.sun.com/software/products/studio/> was used for this submission.

Model PRIMEPOWER850 and model PRIMEPOWER900 are electronically equivalent. This result was measured on model PRIMEPOWER900.