CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer GS1280 7/1300

SPECfp_rate2000 = 19.6

SPECfp_rate_base2000 = 14.8

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Aug-2004 | Software Avail: Jul-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	159	11.7	1	66.6	27.9
171.swim	1	75.8	47.4	1	75.8	47.4
172.mgrid	1	224	9.34	1	148	14.1
173.applu	1	123	19.9	1	113	21.5
177.mesa	1	134	12.1	1	117	13.9
178.galgel	1	122	27.7	1	120	28.1
179.art	1	114	26.5	1	71.1	42.4
183.equake	1	217	6.93	1	72.1	20.9
187.facerec	1	151	14.6	1	135	16.3
188.ammp	1	263	9.72	1	228	11.2
189.lucas	1	117	19.8	1	107	21.8
191.fma3d	1	182	13.4	1	136	17.9
200.sixtrack	1	198	6.44	1	183	6.97
301.apsi	1	183	16.5	1	172	17.5

Hardware

CPU:	Alpha 21364
CPU MHz:	1300
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	2 to 64
Parallel:	No
Primary Cache:	64KB(I)+64KB(D) on chip
Secondary Cache:	1.75MB on chip per CPU
L3 Cache:	None
Other Cache:	None
Memory:	2GB per CPU; 256MB RIMMs
Disk Subsystem:	AdvFS
Other Hardware:	None

Software

Operating System:	Tru64 UNIX V5.1B-1 + PK4
Compiler:	Compaq C V6.5-011-48C5K Program Analysis Tools V2.0 Spike V5.2 (510 USG) HP Fortran V5.5A-3548-48D88 HP Fortran 77 V5.5A-3548-48D88 KAP Fortran V4.3 000607 KAP Fortran 77 V4.1 980926 KAP C V4.1 000607
File System:	MFS, 8GB
System State:	Multi-user

Notes/Tuning Information

```
Baseline   C: cc  -arch ev7 -fast -O4 ONESTEP
     Fortran: f90 -arch ev7 -fast -O5 ONESTEP


Peak:
  All use -g3 -arch ev7 -non_shared ONESTEP
  except these (which use only the tunings shown below):
     173.applu 188.ammp 191.fma3d
  Individual benchmark tuning:
  168.wupwise: kf77 -call_shared -inline all -tune ev67
               -unroll 12 -automatic -align commons -arch ev67
               -fkapargs=' -aggressive=c -fuse
               -fuselevel=1 -so=2 -r=1 -o=1 -interleave
               -ur=6 -ur2=060 ' +PFB
      171.swim: same as base
     172.mgrid: kf90 -call_shared -arch generic -O5 -inline
                manual -nopipeline -transform_loops -unroll 9 -automatic
```

Notes/Tuning Information (Continued)

```
                  -fkapargs='-aggressive=a -fuse -interleave
                  -ur=2 -ur3=5 -cachesize=128,16000 ' +PFB
      173.applu: kf90  -O5 -transform_loops
                 -fkapargs=' -o=0 -nointerleave -ur=14
                 -ur2=260 -ur3=18' +PFB
       177.mesa: kcc -fast -O4 +CFB +IFB
     178.galgel: f90 -O5 -fast -unroll 5 -automatic
        179.art: kcc  -assume whole_program -ldensemalloc
                 -call_shared -assume restricted_pointers
                 -unroll 16 -inline none -ckapargs='
                 -fuse -fuselevel=1 -ur=3' +PFB
     183.equake: cc -call_shared -arch generic -fast -O4
                 -ldensemalloc -assume restricted_pointers
                 -inline speed -unroll 13 -xtaso_short +PFB
    187.facerec: f90 -O4 -nopipeline -inline all
                 -non_shared -speculate all -unroll 7
                 -automatic -assume accuracy_sensitive
                 -math_library fast +IFB
       188.ammp: cc -arch host -O4 -ifo -assume nomath_errno
                 -assume trusted_short_alignment -fp_reorder
                 -readonly_strings -ldensemalloc -xtaso_short
                 -assume restricted_pointers -unroll 9
                 -inline speed +CFB +IFB +PFB
      189.lucas: kf90 -O5 -fkapargs='-ur=1' +PFB
      191.fma3d: kf90 -O4 -transform_loops -fkapargs='-cachesize=128,16000 ' +PFB
   200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
                 -notransform_loops +PFB
      301.apsi: kf90 -O5 -inline none -call_shared -speculate all
                 -align commons -fkapargs=' -aggressive=ab
                 -tune=ev5 -fuse -ur=1 -ur2=60 -ur3=20
                 -cachesize=128,16000'

    Most benchmarks are built using one or more types of
    profile-driven feedback.  The types used are designated
    by abbreviations in the notes:

    +CFB: Code generation is optimized by the compiler, using
          feedback from a training run.  These commands are
          done before the first compile (in phase "fdo_pre0"):

                mkdir /tmp/pp
                rm -f /tmp/pp/${baseexe}*

          and these flags are added to the first and second compiles:

                PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
                PASS2_CFLAGS = -prof_use_feedback -prof_dir /tmp/pp

         (Peak builds use /tmp/pp above; base builds use /tmp/pb.)

    +IFB: Icache usage is improved by the post-link-time optimizer
          Spike, using feedback from a training run.  These commands
          are used (in phase "fdo_postN"):

                mv ${baseexe} oldexe
                spike oldexe -feedback oldexe -o ${baseexe}
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
+PFB: Prefetches are improved by the post-link-time optimizer
      Spike, using feedback from a training run.  These
      commands are used (in phase "fdo_post_makeN"):

           rm -f *Counts*
           mv ${baseexe} oldexe
           pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
           mv oldexe.pixie ${baseexe}

      A training run is carried out (in phase "fdo_runN"), and
      then this command (in phase "fdo_postN"):

           spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}

When Spike is used for both Icache and Prefetch improvements,
only one spike command is actually issued, with the Icache
options followed by the Prefetch options.

vm:
        vm_bigpg_enabled = 1
        vm_bigpg_thresh = 6
        vm_swap_eager = 0
        ubc_maxpercent = 50

proc:
        max_per_proc_address_space = 34359738368
        max_per_proc_data_size = 34359738368
        max_per_proc_stack_size = 34359738368
        max_proc_per_user = 2048
        max_threads_per_user = 4096
        maxusers = 2048
        per_proc_address_space = 34359738368
        per_proc_data_size = 34359738368
        per_proc_stack_size = 34359738368


Portability: galgel: -fixed

Information on UNIX V5.1B Patches can be found at
http://ftp1.service.digital.com/public/unix/v5.1b/

Processes were bound to CPUs using "runon".
```