CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML370 G4 (3.4GHz, Intel Xeon)

SPECfp_rate2000 = 17.3

SPECfp_rate_base2000 = 17.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2004 | Hardware Avail: Aug-2004 | Software Avail: Aug-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	70.2	26.4	1	70.2	26.4
171.swim	1	138	26.1	1	138	26.1
172.mgrid	1	138	15.2	1	138	15.2
173.applu	1	150	16.3	1	145	16.8
177.mesa	1	93.7	17.3	1	93.9	17.3
178.galgel	1	128	26.2	1	128	26.2
179.art	1	209	14.4	1	213	14.2
183.equake	1	76.5	19.7	1	64.9	23.2
187.facerec	1	109	20.2	1	109	20.2
188.ammp	1	224	11.4	1	224	11.4
189.lucas	1	99.4	23.3	1	98.1	23.6
191.fma3d	1	150	16.2	1	150	16.2
200.sixtrack	1	180	7.07	1	180	7.07
301.apsi	1	233	13.0	1	233	13.0

Hardware

CPU:	Intel Xeon (3.4GHz, 1MB L2, 800MHz bus)
CPU MHz:	3400
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip (HT Technology disabled)
CPU(s) orderable:	1,2
Parallel:	--
Primary Cache:	16K micro-ops I + 16KBD on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x512MB DDR2-400
Disk Subsystem:	1x18.2GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	Windows Server 2003 Standard (Build 3790)
Compiler:	Intel C++ Compiler 8.0 Build 20031211Z Intel Fortran Compiler 8.0 build 20040125Z Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
+FDO*: FDO (-QxP not used in PASS1 to enable cross-compilation)

Base tuning for All Programs: -QxP -fast +FDO*
Portability flags:
  178.galgel: -FI /F32000000
Peak tuning:
  168.wupwise:    -QxP  -fast -Qansi_alias                    +FDO*
  171.swim:       -QxP  -fast                        -f77rtl +FDO  ONESTEP=yes
  172.mgrid:      -QxP  -fast -Qansi_alias                    +FDO*
  173.applu:      -QxP  -fast -Qscalar_rep- -Qauto -f77rtl +FDO* ONESTEP=yes
  177.mesa:       -QxP  -fast                                 +FDO* ONESTEP=yes
  178.galgel:     -QxP  -fast                                 +FDO*
  179.art:              -fast -Oa -Qunroll4 -Zp4                    ONESTEP=yes
  183.equake:     -QxP  -fast -Oa -Qrcd                  +FDO*           shlw32M.lib
  187.facerec:    -QaxP -fast -Qunroll1 -Qscalar_rep- -fpp +FDO*
  188.ammp:       basepeak=1
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    189.lucas:       -QaxP -fast
    191.fma3d:       basepeak=1
    200.sixtrack:    -QxP  -fast                              +FDO*
    301.apsi:        -QxP  -fast                    -f77rtl +FDO*
  BIOS Configuration Notes
    HT Technology disabled
```