



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Supermicro
X6DH8-XG2 (3.40 GHz Xeon, 1MB L2 Cache)

SPECint2000 = **1455**
SPECint_base2000 = **1375**

SPEC license #01176 Tested by: Supermicro Inc., San Jose, CA Test date: Jun-2004 Hardware Avail: Jun-2004 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	125	1123	125	1122	
175.vpr	1400	148	946	148	946	
176.gcc	1100	62.6	1757	62.6	1757	
181.mcf	1800	163	1106	160	1126	
186.crafty	1000	80.3	1246	80.5	1243	
197.parser	1800	141	1275	141	1275	
252.eon	1300	78.8	1649	66.2	1963	
253.perlbmk	1800	111	1616	103	1749	
254.gap	1100	61.9	1776	61.9	1776	
255.vortex	1900	76.8	2475	76.8	2475	
256.bzip2	1500	146	1028	140	1074	
300.twolf	3000	258	1161	179	1672	

Hardware

CPU: Intel Xeon (3.4GHz, 800 MHz system bus)
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology enabled)
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 512GB ECC CL3 PC2 3200 DDRII SDRAM
 Disk Subsystem: 1 x 73GB U320 SCSI, 10K RPM
 Other Hardware:

Software

Operating System: Windows 2003 Enterprise Server
 Compiler: Intel C/C++ Compiler 8.0 (20031229Z)
 Microsoft Visual Studio .NET (7.0.9466)
 MicroQuill SmartHeap Library 7.1
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

ONESTEP=yes
 FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

BASE TUNING

C: -QxN -Qipo -O3 +FDO
 C++: -QxN -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxN -Qipo -O3 -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: -QxN -Qipo -O3 +FDO shlw32M.lib
 186.crafty: -QxN -Qipo -O3 -Oa +FDO shlw32M.lib
 197.parser: basepeak=yes
 252.eon: -QxN -Qipo -O3 +FDO
 253.perlbmk: -QxN -Qipo -O3 +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Supermicro
X6DH8-XG2 (3.40 GHz Xeon, 1MB L2 Cache)

SPECint2000 =	1455
SPECint_base2000 =	1375

SPEC license #01176 | Tested by: Supermicro Inc., San Jose, CA | Test date: Jun-2004 | Hardware Avail: Jun-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    basepeak=yes
256.bzip2:    -Qipo      -Oa -Qunroll1 +FDO shlw32M.lib
300.twolf:    -QxN -Qipo -O3      +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.1
              www.microquill.com
```