CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL360 G4 (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 22.8

SPECfp_rate_base2000 = 22.3

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2004 | Hardware Avail: Nov-2004 | Software Avail: Aug-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	92.1	40.3	2	92.1	40.3
171.swim	2	350	20.6	2	350	20.6
172.mgrid	2	219	19.1	2	219	19.1
173.applu	2	285	17.1	2	285	17.1
177.mesa	2	90.6	35.9	2	90.6	35.9
178.galgel	2	214	31.5	2	215	31.4
179.art	2	435	13.9	2	420	14.4
183.equake	2	141	21.4	2	107	28.2
187.facerec	2	148	29.8	2	150	29.4
188.ammp	2	285	17.9	2	285	17.9
189.lucas	2	212	21.9	2	211	22.0
191.fma3d	2	218	22.3	2	218	22.3
200.sixtrack	2	173	14.8	2	173	14.8
301.apsi	2	277	21.8	2	277	21.8

Hardware

CPU:	Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
CPU MHz:	3600
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip (HT Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	16K micro-ops I + 16KBD on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	2x1024MB PC2700 DDR-333
Disk Subsystem:	1x230GB SATA
Other Hardware:	

Software

Operating System:	Windows Server 2003 Standard (Build 3790)
Compiler:	Intel C++ Compiler 8.0 Build 20031211Z Intel Fortran Compiler 8.0 build 20040125Z Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
+FDO*: FDO (-QxP not used in PASS1 to enable cross-compilation)

Base tuning for All Programs: -QxP -fast -Qansi_alias +FDO*
Portability flags:
  178.galgel: -FI /F32000000
Peak tuning:
  168.wupwise:    -QxP  -fast -Qansi_alias                          +FDO*
  171.swim:       -QxP  -fast                       -f77rtl         +FDO  ONESTEP=yes
  172.mgrid:      -QxP  -fast -Qansi_alias                          +FDO*
  173.applu:      -QxP  -fast -Qscalar_rep- -Qauto -f77rtl          +FDO  ONESTEP=yes
  177.mesa:       -QxP  -fast                                       +FDO  ONESTEP=yes
  178.galgel:     -QxP  -fast                                       +FDO  ONESTEP=yes
  179.art:              -fast      -Oa    -Qunroll4 -Zp4                  ONESTEP=yes
  183.equake:     -QxP  -fast -Oa -Qrcd                       +FDO  ONESTEP=yes shlw32M.lib
  187.facerec:    -QaxN -fast -Qunroll1 -Qscalar_rep- -fpp          +FDO  ONESTEP=yes
  188.ammp:       basepeak=1
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    189.lucas:       -QxN-fast
    191.fma3d:       basepeak=1
    200.sixtrack:    -QxP  -fast                                  +FDO*
    301.apsi:        -QxP  -fast                    -f77rtl       +FDO
  BIOS Configuration Notes
    HT Technology disabled
    Adjacent Sector Prefetch disabled
```