



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer OpenPower 720 (1650 MHz, 4CPU, Linux)

SPECfp_rate2000 = 80.8

SPECfp_rate_base2000 = 78.8

SPEC license #: 11 | Tested by: IBM | Test date: Oct-2004 | Hardware Avail: Sep-2004 | Software Avail: Oct-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	136	110	8	129	115
171.swim	8	441	65.2	8	413	69.6
172.mgrid	8	281	59.4	8	281	59.5
173.applu	8	416	46.8	8	413	47.2
177.mesa	8	205	63.4	8	201	64.7
178.galgel	8	155	174	8	135	200
179.art	8	76.8	314	8	77.1	313
183.equake	8	120	101	8	119	101
187.facerec	8	194	91.0	8	180	97.7
188.amp	8	372	54.9	8	383	53.4
189.lucas	8	335	55.4	8	335	55.4
191.fma3d	8	322	60.5	8	331	58.8
200.sixtrack	8	218	46.8	8	217	47.1
301.apsi	8	365	66.1	8	355	68.0

Hardware

CPU: POWER5
 CPU MHz: 1650
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (SMT on)
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified (on chip)/chip
 L3 Cache: 36MB unified (off chip)/DCM, 2 DCM/SUT
 Other Cache: None
 Memory: 16x1 GB
 Disk Subsystem: 1X72GB SCSI, 15K RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 9 for IBM POWER
 Compiler: XL Fortran Enterprise Edition Version 9.1 for Linux
 XL C/C++ Enterprise Edition Version 7.0 for Linux
 Other Software: IBM ESSL for Linux, Version 4 Release 2
 File System: ReiserFS
 System State: Single-User

Notes/Tuning Information

Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
 -qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:

C:
 -O5 -qpdf1/pdf2
 Fortran:
 -O5 -qpdf1/pdf2

Floating Point Peak Flags

168.wupwise
 -O5 -qarch=pwr3 -qtune=pwr3
 171.swim
 -O3 -qarch=pwr5 -qtune=pwr5 -qhot
 172.mgrid



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer OpenPower 720 (1650 MHz, 4CPU, Linux)

SPECfp_rate2000 = 80.8

SPECfp_rate_base2000 = 78.8

SPEC license #: 11 | Tested by: IBM | Test date: Oct-2004 | Hardware Avail: Sep-2004 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
-04 -qarch=pwr4 -qtune=pwr4
173.applu
-05 -q64 -qarch=pwr4 -qtune=pwr4
177.mesa: -qpdf1/pdf2
-04 -qarch=pwr4 -qtune=pwr4
178.galgel
-05 -qessl -lessl
"FC invoked as xlf_r"
179.art
-05 -qarch=pwr5 -qtune=pwr5
183.quake
-05 -qarch=pwr5 -qtune=pwr5
187.facerec: -qpdf1/pdf2
-03 -qarch=pwr5 -qtune=pwr5 -qhot
188.ammp
-03 -qarch=pwr4 -qtune=pwr4
189.lucas
-03 -qarch=pwr5 -qtune=pwr5
191.fma3d: -qpdf1/pdf2
-04 -qarch=pwr5 -qtune=pwr5
200.sixtrack
-03 -qarch=pwr5 -qtune=pwr5
301.apsi
-05 -qarch=pwr5 -qtune=pwr5 -qessl -lessl
"F77 invoked as xlf_r"
```

C: invoked as cc except where noted as xlc

Fortran 77 and 90: Fortran for Linux invoked as xlf90

ESSL: Engineering and Scientific Subroutine Library

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

Stack size set to unlimited using the command "ulimit -s unlimited"

Submitted_by: Kevin Lu <kevinlu@us.ibm.com>

Submitted: Mon Oct 18 22:24:01 2004

Submission: cpu2000-20041018-03449.sub