CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K8QS Pro, (S4882), AMD Opteron (TM) 850

SPECfp_rate2000 = 42.2

SPECfp_rate_base2000 = 37.9

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Oct-2004 | Hardware Avail: Jul-2004 | Software Avail: Aug-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	90.9	40.8	2	76.7	48.4
171.swim	2	119	60.4	2	119	60.2
172.mgrid	2	113	37.1	2	102	41.0
173.applu	2	130	37.6	2	109	44.8
177.mesa	2	96.0	33.8	2	69.0	47.0
178.galgel	2	102	66.0	2	94.1	71.5
179.art	2	146	41.2	2	107	56.3
183.equake	2	86.4	34.9	2	86.4	34.9
187.facerec	2	101	43.7	2	93.0	47.4
188.ammp	2	157	32.4	2	150	34.1
189.lucas	2	122	38.1	2	105	44.2
191.fma3d	2	143	34.2	2	138	35.2
200.sixtrack	2	151	16.9	2	150	17.0
301.apsi	2	162	37.3	2	161	37.6

Hardware

CPU:	AMD Opteron (TM) 850
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x512 MB PC3200 CL3.0 ECC Reg
Disk Subsystem:	SCSI, Seagate Cheetah ST336753LW, U320, 15K rpm
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Sever for AMD64 (SP3)
Compiler:	PathScale EKO Compiler Suite, Release 1.3
File System:	Linux/ext3
System State:	Multi-user SuSE Run level 3

Notes/Tuning Information

```
  +FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata
  +ACML is linking with AMD Core Math Library

  Baseline optimization
    C programs:       -Ofast -WOPT:mem_opnds=on +FDO
    Fortran programs: -Ofast -LNO:fusion=2
  Portability Flags:
    178.galgel: -fixedform

 Peak Tuning:
  168.wupwise: -Ofast -LNO:prefetch_ahead=5:prefetch=3
               -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
               -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
               -INLINE:aggressive=on
  171.swim:    -Ofast -LNO:fusion=2:prefetch=2
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 172.mgrid:   -O3 -LNO:fusion=2:blocking=off:prefetch=2
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
              -CG:gcm=off:cflow=off
 173.applu:   -Ofast -CG:local_fwd_sched=on
              -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
              -OPT:ro=3 -TENV:X=3 -WOPT:val=2
 177.mesa:    -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
 178.galgel:  -Ofast -OPT:fast_complex -CG:load_exe=0:use_movlpd=on +ACML
 179.art:     -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
 183.equake:  basepeak = true
 187.facerec:  -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
               -LNO:fusion=2:prefetch=0 +FDO -IPA:plimit=1800
 188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3 -LNO:prefetch=0
           -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -CG:prefetch=off:load_exe=2:local_fwd_sched
           -TENV:X=4 -WOPT:retype_expr=on +FDO
 191.fma3d: -O2 -ipa -WOPT:mem_opnds=on:retype_expr=on -OPT:Ofast:IEEE_arith=3:ro=3
            +FDO -IPA:pu_reorder=1
 200.sixtrack:= -Ofast +FDO
 301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
 BIOS rev. 1.00
 Taskset utility used to bind CPU(s) to processes
 All memory slots populated on CPU0 and CPU1
 The tested system can be assembled using an SSI MEB footprint case,
 such as the CCSI RC0352 3U rackmount case, and a Tyan recommended 660W EPS-12V
 power supply, such as the Enermax 660W power supply (PEG851AX-VH)
```