CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity rx2620-2 (1.3GHz/3MB, Itanium 2)

SPECfp_rate2000 = 25.9

SPECfp_rate_base2000 = 25.9

SPEC license #: 3 | Tested by: HP Richardson | Test date: Dec-2004 | Hardware Avail: Dec-2004 | Software Avail: Nov-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	61.4	30.2	1	61.4	30.2
171.swim	1	74.2	48.5	1	74.2	48.5
172.mgrid	1	75.5	27.7	1	75.5	27.7
173.applu	1	62.2	39.2	1	62.2	39.2
177.mesa	1	136	11.9	1	136	11.9
178.galgel	1	54.6	61.6	1	54.6	61.6
179.art	1	25.4	119	1	25.4	119
183.equake	1	44.9	33.6	1	44.9	33.6
187.facerec	1	126	17.4	1	126	17.4
188.ammp	1	180	14.1	1	180	14.1
189.lucas	1	115	20.2	1	115	20.2
191.fma3d	1	151	16.1	1	151	16.1
200.sixtrack	1	85.2	15.0	1	85.2	15.0
301.apsi	1	282	10.7	1	282	10.7

Hardware

CPU:	Intel Itanium 2 (1.3 GHz/3MB, 400MHz FSB)
CPU MHz:	1300
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	no
Primary Cache:	16KBI + 16KBD on chip, per core
Secondary Cache:	256KB (I+D) on chip, per core
L3 Cache:	3.0MB (I+D) on chip, per core
Other Cache:	N/A
Memory:	24GB (12x2GB DIMMs)
Disk Subsystem:	1x36GB 15K SCSI
Other Hardware:	N/A

Software

Operating System:	Red Hat Linux Advanced Server release 3.0AS (Update 3)
Compiler:	Intel C++ Compiler 8.1 for Linux (Build 20041021) Intel Fortran Compiler 8.1 for Linux (Build 20041021)
File System:	ext3
System State:	Multi-user

Notes/Tuning Information

```
Base tuning flags:
        C programs: -fast -ansi_alias +FDO -IPF_fp_relaxed
   Fortran programs: -fast +FDO -IPF_fp_relaxed

Portability:
        178.galgel:  -FI
        187.facerec: srcalt=AllocShape

Peak flags same as baseline (basepeak=true set globally)
+FDO: PASS1=-prof_gen  PASS2=-prof_use

Note:
  EFI command "cpuconfig" used prior to booting to
  deconfigure other processors if necessary
```