CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 2500 (1.6GHz)

SPECint_rate2000 = 9.80

SPECint_rate_base2000 = 8.57

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Dec-2004 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	198	8.21	1	171	9.51
175.vpr	1	221	7.33	1	216	7.52
176.gcc	1	150	8.53	1	116	11.0
181.mcf	1	498	4.19	1	286	7.30
186.crafty	1	114	10.1	1	95.9	12.1
197.parser	1	277	7.53	1	246	8.50
252.eon	1	126	12.0	1	126	12.0
253.perlbmk	1	223	9.36	1	204	10.2
254.gap	1	170	7.51	1	154	8.31
255.vortex	1	137	16.1	1	130	16.9
256.bzip2	1	228	7.64	1	221	7.89
300.twolf	1	377	9.24	1	355	9.79

Hardware

CPU:	UltraSPARC IIIi
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	1MB(I+D) off chip
L3 Cache:	None
Other Cache:	None
Memory:	4GB (4x1GB DIMM)
Disk Subsystem:	1 x 146GB 10K RPM SCSI
Other Hardware:	None

Software

Operating System:	Solaris 10
Compiler:	Sun Studio 9
File System:	ufs
System State:	Multi-User

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  CXX: CC

Integer base flags:
     -fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
 ONESTEP=yes and feedback for all benchmarks

 164.gzip:    -xO4  -xbuiltin=%all -xtarget=native -xalias_level=std
             -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30, -Qeps:do_spec_load=1
 175.vpr:     -fast -xalias_level=std -xipo=2
             -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100,-Qeps:do_spec_load=1 -lmopt -lm
 176.gcc:     -fast -xipo=2 -ll2amm
 181.mcf:     -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
              -W2,-Apf:llist=3:noinnerllist
 186.crafty:  -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
              Feedback adds -xlinkopt in PASS2
 197.parser:  -fast -xipo=2 -xalias_level=strong
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                -Wc,-Qgsched-T6,-Qipa:valueprediction
 252.eon:       basepeak=yes
 253.perlbmk:   -xO5 -xtarget=native  -xmemalign=4s -xipo -Wc,-Qeps:enabled=1
                -Qeps:ws=8, -xalias_level=std -xsafe=mem -Wc,-Qiselect-funcalign=32,
               -Qicache-chbab=1 -Wc,-Qiselect-sw_pf_tbl_th=20,-Qeps:do_spec_load=1 -xprefetch=no
 254.gap:       -fast -xipo=2 -xalias_level=strong -xvector
                -xprefetch_level=3 -W2,-Abcopy
 255.vortex:    -fast -xrestrict -xipo=2
                -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
                -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
                -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
 256.bzip2:     -fast -xipo -xalias_level=strong -xrestrict
                -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
 300.twolf:     -fast -xalias_level=strong -xsafe=mem -xipo=2
                -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

Feedback is done as follows, unless otherwise noted:
 fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
 PASS1:     -xprofile=collect:./feedback
 PASS2:     -xprofile=use:./feedback

Portability:
 176.gcc:       -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty:    -DSUN
 252.eon:       -library=iostream
                srcalt = fmax_errno
 253.perlbmk:   -DSPEC_CPU2000_SOLARIS
 254.gap:       -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
                -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"
  MPSSHEAP=512K
  MPSSSTACK=512K
  LD_PRELOAD=mpss.so.1

Kernel Parameters (/etc/system):
 autoup=900
 tune_t_fsflushr=1

Only one CPU in the system
```