CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V210 (1336MHz)

SPECfp_rate2000 = 25.9

SPECfp_rate_base2000 = 23.2

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Dec-2004 | Hardware Avail: Jan-2005 | Software Avail: Jan-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	146	25.5	2	146	25.5
171.swim	2	380	19.0	2	192	37.4
172.mgrid	2	276	15.1	2	277	15.1
173.applu	2	254	19.2	2	209	23.3
177.mesa	2	189	17.2	2	163	19.9
178.galgel	2	166	40.6	2	142	47.3
179.art	2	27.2	222	2	25.7	235
183.equake	2	90.3	33.4	2	83.4	36.2
187.facerec	2	120	36.7	2	119	37.0
188.ammp	2	449	11.4	2	423	12.1
189.lucas	2	263	17.6	2	263	17.6
191.fma3d	2	369	13.2	2	332	14.7
200.sixtrack	2	243	10.5	2	234	10.9
301.apsi	2	333	18.1	2	332	18.2

Hardware

CPU:	UltraSPARC IIIi
CPU MHz:	1336
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	1MB(I+D) on chip
L3 Cache:	None
Other Cache:	None
Memory:	8GB 16-way interleaved
Disk Subsystem:	1 x 73GB
Other Hardware:	None

Software

Operating System:	Solaris 10
Compiler:	Sun Studio 9
File System:	ufs
System State:	Multi-User

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  CXX: CC
  F90: f90
  F77: f90

Floating point base flags:
  C:  -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
  F90:  -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:
 ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

 168.wupwise: basepeak = yes
 171.swim:    -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
              -Qoption iropt -Atile:skewp,-Ainline:cs=700
              (no feedback)
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 172.mgrid:   -fast -xipo=2
 173.applu:   -fast -xipo=2
              -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
              -Qoption iropt -Aujam:inner=g
 177.mesa:    -fast -xipo=2 -xalias_level=strong -xrestrict
              -Wc,-Qms_pipe+unoovf
 178.galgel:  -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
              RM_SOURCES=lapak.f90
 179.art:     -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
 183.equake:  -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
 187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
 188.ammp:    -fast -xarch=v9b -xipo=2 -xalias_level=std -lmopt -lm
 189.lucas:   basepeak = yes
 191.fma3d:   -fast -xipo=2 -stackvar -xprefetch_level=3
              -Qoption iropt -Apf:pdl=1
 200.sixtrack:-xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
              -xprefetch=no
 301.apsi:    -fast -xipo=2

Feedback is done as follows, unless otherwise noted:
 fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
 PASS1:     -xprofile=collect:./feedback
 PASS2:     -xprofile=use:./feedback

Portability:
 178.galgel:  -e -fixed

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"
  MPSSHEAP=512K
  MPSSSTACK=512K
  LD_PRELOAD=mpss.so.1

Kernel Parameters (/etc/system):
 autoup=900
 tune_t_fsflushr=1
Processes were bound to CPUs using submit=pbind
```