



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 252)

SPECint_rate2000 = 20.2
SPECint_rate_base2000 = 18.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	88.9	18.3	1	88.8	18.3
175.vpr	1	114	14.3	1	111	14.6
176.gcc	1	62.5	20.4	1	62.5	20.4
181.mcf	1	250	8.37	1	158	13.2
186.crafty	1	44.2	26.3	1	44.2	26.2
197.parser	1	153	13.6	1	125	16.7
252.eon	1	57.6	26.2	1	48.4	31.1
253.perlbnk	1	102	20.5	1	93.8	22.3
254.gap	1	68.5	18.6	1	65.4	19.5
255.vortex	1	75.7	29.1	1	69.5	31.7
256.bzip2	1	106	16.5	1	106	16.5
300.twolf	1	220	15.8	1	163	21.3

Hardware

CPU: AMD Opteron (TM) 252
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC3200 DDR 400
 Disk Subsystem: 1x36.4GB Ultra320 SCSI
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 for AMD64
 SuSE kernel 2.6.5-7.97-smp
 Compiler: PathScale EKO Compiler Suite, Release 1.4
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -O3 -ipa +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
           -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
           -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files
 300.twolf: -DHAVE_SIGNED_CHAR
Peak tuning:
 164.gzip: -Ofast +FDO
 175.vpr: -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000 +FDO
 loader: -INLINE:aggressive=on
         -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
 176.gcc: basepeak=true
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 252)

SPECint_rate2000 = 20.2
SPECint_rate_base2000 = 18.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```
186.crafty: -Ofast +FDO
197.parser: -O3 -ipa -m32 +FDO
  loader:   -IPA:ctype=on
252.eon:    -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
          -TENV:X=4:frame_pointer=off -fno-exceptions -LNO:fu=10:full_unroll_outer=on
          +FDO
  loader:   -IPA:plimit=4000:pu_reorder=1
253.perlbmk: -O3 -ipa +FDO
  loader:   -IPA:plimit=10000
254.gap:    -O3 -ipa -OPT:transform_to_memlib=on
255.vortex: -Ofast -IPA:space=70:plimit=3000
          -OPT:goto=off:unroll_analysis=off:unroll_size=0:unroll_times_max=8
          -LNO:opt=0 -TENV:X=4 +FDO
256.bzip2:  basepeak=true
300.twolf:  -O2 -OPT:unroll_times_max=8:unroll_size=256:alias=disjoint:Ofast
          -CG:gcm=off:p2align_freq=100000 -WOPT:mem_opnds=on -m32 +FDO
```

BIOS Configuration Notes
Node Interleaving Disabled