CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Pogo Linux, PerformanceWare 3566, AMD Opteron (TM) 852

SPECint_rate2000 = 40.1

SPECint_rate_base2000 = 37.8

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Feb-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	98.4	33.0	2	98.4	33.0
175.vpr	2	105	30.9	2	102	31.9
176.gcc	2	59.8	42.7	2	59.3	43.0
181.mcf	2	180	23.2	2	149	28.0
186.crafty	2	60.1	38.6	2	54.2	42.8
197.parser	2	113	36.9	2	119	35.2
252.eon	2	55.5	54.3	2	46.7	64.6
253.perlbmk	2	107	39.1	2	107	39.1
254.gap	2	62.0	41.2	2	62.0	41.2
255.vortex	2	76.6	57.6	2	76.6	57.6
256.bzip2	2	115	30.3	2	113	30.9
300.twolf	2	177	39.3	2	144	48.4

Hardware

CPU:	AMD Opteron (TM) 852
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x1024 MB PC3200 (MICRON) CL3 ECC Reg
Disk Subsystem:	SCSI, Seagate Cheetah Ultra320 ST373307LC, 10K rpm
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003, Enterprise Edition
Compiler:	Intel C++ 8.0 build 20040714Z Microsoft Visual Studio .NET 7.0.9466 (libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
shlW32M7.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Portability:
  176.gcc:      -Dalloca=_alloca /F10000000
  186.crafty:   -DNT_i386
  253.perlbmk:  -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap:      -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Baseline C:   -fast -arch:SSE2 -Oi- +FDO
Baseline C++: -fast -arch:SSE2 -GX -GR
Peak Tuning:
164.gzip:     basepeak=yes
175.vpr:      -fast -arch:SSE2 +FDO
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
176.gcc:      -fast -arch:SSE2 +FDO -Oi- -Qunroll3
181.mcf:      -fast -QaxN      +FDO
186.crafty:   -fast -arch:SSE2 +FDO
197.parser:         -arch:SSE2 +FDO -Oi- -Qipo
252.eon:      -fast -arch:SSE2 +FDO -Qansi_alias
             -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
253.perlbmk:  basepeak=yes
254.gap:      basepeak=yes
255.vortex:   basepeak=yes
256.bzip2:    -fast -Qunroll2
300.twolf:    -fast -arch:SSE2 +FDO      -Qunroll3 shlW32M7.lib -Qansi_alias
Bios Rev 2.32.3.1
All memory slots populated on all CPU(s)
Physical Address Extension (PAE) enabled
```