CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
H8DAR-8 (AMD Opteron (TM) 252)

SPECfp2000 = 1704

SPECfp_base2000 = 1600

SPEC license #01176 | Tested by: supermicro | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jul-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	60.8	2630	60.8	2630
171.swim	3100	158	1965	142	2181
172.mgrid	1800	129	1395	129	1395
173.applu	2100	159	1319	137	1534
177.mesa	1400	74.5	1879	69.6	2012
178.galgel	2900	114	2547	100.0	2901
179.art	2600	152	1711	146	1783
183.equake	1300	85.1	1528	85.1	1528
187.facerec	1900	102	1862	98.9	1921
188.ammp	2200	179	1227	161	1365
189.lucas	2000	121	1647	105	1907
191.fma3d	2100	151	1390	137	1537
200.sixtrack	1100	139	791	139	791
301.apsi	2600	178	1462	178	1462



Hardware

CPU:	AMD Opteron (TM) 252
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4 x 1024MB PC3200 REG ECC CL3 DDR SDRAM
Disk Subsystem:	1 X 300GB IDE
Other Hardware:	None

Software

Operating System:	Windows Enterprise Server 2003
Compiler:	Intel C++ 8.0 build 20040714Z, Intel Fortran 8.1 build 20041019Z, PGI Fortran compiler 5.2-4 for Windows XP, AMD Core Math library Version 2.1 (ACML), Microsoft Visual Studio .NET 7.0.9466 (libraries), MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
Tested by Supermicro
  +FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
  +ACML is linking with AMD Core Math Library V2.1
  ONESTEP is set for all peak runs.
  ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
  pgf90 is the PGI Fortran compiler.
  The Intel C++ 8.0 and the Intel Fortran 8.1 compilers are setup in the following order:
     "c:program filesintel ortrancompiler80ia32 inifortvars.bat"
     "c:program filesintelcppcompiler80ia32 iniclvars.bat"
  To make sure that the correct libraries are selected, the following link option is
  added for the peak runs where Intel Fortran 8.1 compiler is used:
      LDOPT = -Fe$@ -link -LIBPATH:"c:program filesintel ortrancompiler80ia32lib"
   (denoted by +LIBPATH:INTEL8.1 in the optimization flags listed below)
  Portability:
    178.galgel: -Mfixed
  Baseline: C      : icl   -fast -arch:SSE2 -QaxW +FDO
  Baseline: Fortran: pgf90 -fastsse -Mipa=fast,inline
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Peak tuning:
168.wupwise:       pgf90 basepeak=yes
171.swim:          ifort -Qipo  -O3  -QaxN -QxW +FDO -Qunroll0     +LIBPATH:INTEL8.1
172.mgrid:         pgf90 basepeak=yes
173.applu:         ifort -Qipo  -O3  -QaxN -QxW +FDO -auto         +LIBPATH:INTEL8.1
177.mesa:          icl   -Qipo -arch:SSE2       +FDO -Qunroll1 -Qansi_alias
                       -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
179.art:           icl   -Qipo             -Zp4 +FDO
183.equake:        icl   basepeak=yes
Tested system can be used with a 420W (minimum) ATX power supply
187.facerec:       ifort -Qipo             -QxW +FDO -Qunroll3     +LIBPATH:INTEL8.1
                       -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ammp:          icl   -Oa   -arch:SSE2  -Zp4      -Qansi_alias
189.lucas:         ifort -Qipo             -QxW      -Qunroll1     +LIBPATH:INTEL8.1
191.fma3d:         ifort -Qipo       -QaxN -QxW +FDO -Qansi-alias- +LIBPATH:INTEL8.1
200.sixtrack:      pgf90 basepeak=yes
301.apsi:          pgf90 basepeak=yes
```