CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.0 GHz Intel Xeon)

SPECfp_rate2000 = 28.1

SPECfp_rate_base2000 = 27.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	85.0	43.7	2	85.0	43.7
171.swim	2	300	24.0	2	300	24.0
172.mgrid	2	190	22.0	2	190	22.0
173.applu	2	234	20.8	2	234	20.8
177.mesa	2	107	30.3	2	107	30.3
178.galgel	2	118	57.2	2	117	57.3
179.art	2	94.7	63.7	2	94.7	63.7
183.equake	2	93.4	32.3	2	93.4	32.3
187.facerec	2	136	32.5	2	136	32.5
188.ammp	2	247	20.7	2	209	24.4
189.lucas	2	200	23.3	2	199	23.3
191.fma3d	2	222	21.9	2	222	21.9
200.sixtrack	2	203	12.5	2	202	12.7
301.apsi	2	272	22.2	2	272	22.2

Hardware

CPU:	Intel Xeon (3.0 GHz, 2MB L2, 800MHz system bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache:	2048KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6 x 512MB ECC DDR-333 SDRAM
Disk Subsystem:	1 x 80GB 7200RPM SATA HDD
Other Hardware:	

Software

Operating System:	Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler:	Intel C++ Build 20041019Z and Fortran Compiler 8.1 Build 20040802Z Microsoft Visual Studio .Net 2003(7.1.3091, for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning for Fortran Programs :  -fast -Qansi_alias +FDO
177.mesa:Base for C Program: -fast +FDO shlw32M.lib
179.art:Base for C Program: -fast +FDO shlw32M.lib
183.equake:Base for C Program: -fast +FDO shlw32M.lib
188.ammp:Base for C Program: -fast +FDO shlw32M.lib
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -fast -Qansi_alias +FDO
171.swim:     -fast -Qansi_alias +FDO
172.mgrid:    -fast -Qansi_alias +FDO
173.applu:  basepeak=yes
177.mesa:   basepeak=yes
178.galgel:   -fast -Qansi_alias +FDO
179.art:      basepeak=yes
183.equake:   -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
187.facerec:  basepeak=yes
188.ammp:     -Oa -QxP
189.lucas:    -fast -Qprefetch- +FDO
191.fma3d:    basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi:     -fast +FDO
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at http://www.acer.com
```