CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R710 (3.0 GHz Intel Xeon)

SPECfp2000 = 1474

SPECfp_base2000 = 1457

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	69.5	2301	69.5	2301
171.swim	3100	144	2159	144	2159
172.mgrid	1800	139	1295	139	1295
173.applu	2100	157	1340	157	1340
177.mesa	1400	105	1336	105	1336
178.galgel	2900	136	2129	136	2129
179.art	2600	101	2581	101	2581
183.equake	1300	66.3	1961	66.3	1959
187.facerec	1900	119	1598	119	1598
188.ammp	2200	287	766	247	892
189.lucas	2000	108	1845	108	1845
191.fma3d	2100	164	1284	164	1284
200.sixtrack	1100	204	539	203	543
301.apsi	2600	260	1001	260	1001



Hardware

CPU:	Intel Xeon (3.0 GHz, 1MB L2, 800MHz system bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache:	1024KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6 x 512MB ECC DDR2-400 SDRAM
Disk Subsystem:	1 x 73GB 10000RPM U320 SCSI HDD
Other Hardware:	

Software

Operating System:	Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler:	Intel C++ Build 20041019Z and Fortran Compiler 8.1 Build 20040802Z Microsoft Visual Studio .Net 2003(7.1.3091, for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning for Fortran Programs :  -fast -Qansi_alias +FDO
177.mesa:Base for C Program: -fast +FDO shlw32M.lib
179.art:Base for C Program: -fast +FDO shlw32M.lib
183.equake:Base for C Program: -fast +FDO shlw32M.lib
188.ammp:Base for C Program: -fast +FDO shlw32M.lib
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -fast -Qansi_alias +FDO
171.swim:     -fast -Qansi_alias +FDO
172.mgrid:    -fast -Qansi_alias +FDO
173.applu:  basepeak=yes
177.mesa:   basepeak=yes
178.galgel:   -fast -Qansi_alias +FDO
179.art:      basepeak=yes
183.equake:   -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
187.facerec:  basepeak=yes
188.ammp:     -Oa -QxP
189.lucas:    -fast -Qprefetch- +FDO
191.fma3d:    basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi:     -fast +FDO
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at http://www.acer.com
```