CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL385 (AMD Opteron (TM) 275)

SPECfp_rate2000 = 21.8

SPECfp_rate_base2000 = 19.9

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2005 | Hardware Avail: Jul-2005 | Software Avail: Apr-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	68.3	27.2	1	58.3	31.8
171.swim	1	132	27.3	1	132	27.2
172.mgrid	1	115	18.1	1	106	19.7
173.applu	1	115	21.2	1	106	23.0
177.mesa	1	80.4	20.2	1	76.3	21.3
178.galgel	1	102	32.8	1	90.6	37.1
179.art	1	113	26.7	1	79.6	37.9
183.equake	1	86.5	17.4	1	80.7	18.7
187.facerec	1	84.2	26.2	1	80.9	27.2
188.ammp	1	170	15.0	1	157	16.2
189.lucas	1	104	22.3	1	104	22.3
191.fma3d	1	148	16.4	1	143	17.1
200.sixtrack	1	172	7.42	1	147	8.66
301.apsi	1	181	16.7	1	177	17.1

Hardware

CPU:	AMD Opteron (TM) 275
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048MB PC3200 DDR CL3.0
Disk Subsystem:	1x36GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	SuSE Linux Enterprise Server 9 (x86_64) SP 1 SuSE kernel 2.6.5-7.139-default
Compiler:	PathScale EKO Compiler Suite, Release 2.1 AMD Core Math Library 2.5.1
File System:	Linux/ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
  178.galgel:    -fixedform
Peak tuning:
  168.wupwise:   -Ofast -LNO:prefetch_ahead=5:prefetch=3
                -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
                 -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
                 -INLINE:aggressive=on
  171.swim:      -Ofast -LNO:fusion=2
  172.mgrid:     -O3 -LNO:fusion=2:blocking=off
                -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
  173.applu:     -Ofast -CG:local_fwd_sched=on
                 -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
                 -OPT:ro=3 -TENV:X=3 -WOPT:val=2
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
  178.galgel:    -Ofast -OPT:fast_complex -CG:use_movlpd=on RM_SOURCES=lapak.f90 +ACML
  179.art:       -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
  183.equake:    -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on -m32
  187.facerec:   -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
                 -LNO:fusion=2 -IPA:plimit=1500 +FDO
  188.ammp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
                 -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
  189.lucas:     -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
  191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
                 -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
  200.sixtrack:  -Ofast -CG:load_exe=1 +FDO
  301.apsi:      -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
BIOS Configuration Notes
  Node Interleaving is Disabled
Other Configuration Notes
   Taskset utility used to bind process to CPU(s)
   Single-processor kernel was used
```