CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN S2865 K8E Tomcat, AMD Opteron (TM) 144

SPECint2000 = 1319

SPECint_base2000 = 1202

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	127	1099	127	1099
175.vpr	1400	141	994	136	1031
176.gcc	1100	84.4	1303	83.8	1313
181.mcf	1800	255	705	167	1081
186.crafty	1000	64.9	1541	65.1	1537
197.parser	1800	197	914	169	1064
252.eon	1300	75.5	1721	69.0	1885
253.perlbmk	1800	144	1253	127	1417
254.gap	1100	88.4	1245	87.0	1264
255.vortex	1900	98.7	1926	90.1	2110
256.bzip2	1500	138	1086	138	1086
300.twolf	3000	261	1149	221	1359



Hardware

CPU:	AMD Opteron (TM) 144 (939-pin)
CPU MHz:	1800
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x512 MB, DDR400 CL2.0
Disk Subsystem:	IDE, Western Digital WD2000JB, 7200 rpm
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 9 (SP2) for AMD64
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.1
File System:	Linux/ext3
System State:	Multi-user, run level 3

Notes/Tuning Information

```
Tested by AMD

 +FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata

 Baseline optimization flags:
   C programs:       -Ofast +FDO
   C++ programs:     -Ofast +FDO

 Portability Flags:
   176.gcc:      srcalt 64bitgcc
   186.crafty:  -DLINUX_i386
   252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt fmax_errno
   253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
                -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
   254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
                -DSYS_HAS_SIGNAL_PROTO  -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
                -DSPEC_CPU2000_LP64
   255.vortex:  -DSPEC_CPU2000_LP64 srcalt closed_files

 Peak Tuning:
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  164.gzip:     basepeak = true
  175.vpr:     -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000
               -INLINE:aggressive=on -IPA:plimit=10000:callee_limit=5000
               +FDO
  176.gcc:     -O3 -ipa -OPT:goto=off +FDO
  181.mcf:     -O3 -ipa -IPA:field_reorder=on -m32 +FDO
  186.crafty:  -O3 -OPT:goto=off +FDO
  197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
  252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
               -TENV:X=4:frame_pointer=off -fno-exceptions
               -LNO:fu=10:full_unroll_outer=on -IPA:plimit=4000 +FDO
  253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
               -fno-math-errno -IPA:plimit=10000 +FDO
  254.gap:     -Ofast -WOPT:aggstr=off +FDO
  255.vortex:  -Ofast -OPT:goto=off -IPA:plimit=1800 -CG:p2align=on
               +FDO
  256.bzip2:    basepeak = true
  300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
               -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
               -WOPT:mem_opnds=on -m32 +FDO
The tested system can be assembled using a standard ATX footprint, an Antec True 550
Watt EPS12V power supply, and a PCI or PCIe graphics card.
All memory slots were populated with Corsair CMX512-3200XL.
Memory timings manually set in BIOS: CAS=2, TRCD=2, TRAS=5, TRP=2
BIOS version 1.01
```