CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL35p (AMD Opteron (TM) 275)

SPECfp_rate2000 = 66.1

SPECfp_rate_base2000 = 61.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	77.2	96.2	4	72.3	103
171.swim	4	275	52.3	4	276	52.2
172.mgrid	4	172	48.6	4	167	50.2
173.applu	4	148	66.0	4	138	70.8
177.mesa	4	81.6	79.6	4	77.0	84.4
178.galgel	4	132	102	4	128	105
179.art	4	156	77.5	4	105	115
183.equake	4	131	46.1	4	120	50.3
187.facerec	4	107	82.6	4	104	84.5
188.ammp	4	178	57.3	4	166	61.5
189.lucas	4	183	50.6	4	181	51.3
191.fma3d	4	184	52.9	4	179	54.4
200.sixtrack	4	172	29.7	4	147	34.6
301.apsi	4	198	61.0	4	194	62.2

Hardware

CPU:	AMD Opteron (TM) 275
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048MB PC3200 CL3.0
Disk Subsystem:	1x60GB ATA100 5400RPM
Other Hardware:	

Software

Operating System:	SuSE Linux Enterprise Server 9 (x86_64) SP 1 SuSE kernel 2.6.5-7.139-smp
Compiler:	PathScale EKO Compiler Suite, Release 2.1 AMD Core Math Library 2.5.1
File System:	Linux/ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
  178.galgel:    -fixedform
Peak tuning:
  168.wupwise:   -Ofast -LNO:prefetch_ahead=5:prefetch=3
                -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
                 -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
                 -INLINE:aggressive=on
  171.swim:      -Ofast -LNO:fusion=2
  172.mgrid:     -O3 -LNO:fusion=2:blocking=off
                -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
  173.applu:     -Ofast -CG:local_fwd_sched=on
                 -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
                 -OPT:ro=3 -TENV:X=3 -WOPT:val=2
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
    178.galgel:    -Ofast -OPT:fast_complex RM_SOURCES=lapak.f90 +ACML
    179.art:       -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
    183.equake:    -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on -m32
    187.facerec:   -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
                   -LNO:fusion=2 -IPA:plimit=1500 +FDO
    188.ammp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
                   -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
    189.lucas:     -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
    191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
                   -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
    200.sixtrack:  -Ofast -CG:load_exe=1 +FDO
    301.apsi:      -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
  BIOS Configuration Notes
    Node Interleaving is Disabled
  Other Configuration Notes
     Taskset utility used to bind process to CPU(s)
```