CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8QSD Pro (S4882-D), AMD Opteron (TM) 254

SPECint_rate2000 = 43.5

SPECint_rate_base2000 = 39.2

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	82.8	39.2	2	82.8	39.2
175.vpr	2	106	30.6	2	103	31.6
176.gcc	2	58.4	43.7	2	57.6	44.3
181.mcf	2	233	17.9	2	148	28.2
186.crafty	2	41.8	55.5	2	41.5	55.9
197.parser	2	141	29.7	2	115	36.2
252.eon	2	48.3	62.5	2	44.4	68.0
253.perlbmk	2	95.5	43.7	2	85.2	49.0
254.gap	2	61.2	41.7	2	60.2	42.4
255.vortex	2	70.0	63.0	2	64.2	68.7
256.bzip2	2	103	33.7	2	103	33.7
300.twolf	2	198	35.1	2	154	45.3

Hardware

CPU:	AMD Opteron (TM) 254
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x512 MB, DDR400 ECC Reg CL2.5
Disk Subsystem:	SATA, Western Digital WD740GD, 74GB 10000 rpm
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 9 SP2 for AMD64
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.1
File System:	Linux/ext3
System State:	Multi-user, run level 3

Notes/Tuning Information

```
Tested by AMD

 +FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata

 Baseline optimization flags:
   C programs:       -Ofast +FDO
   C++ programs:     -Ofast +FDO

 Portability Flags:
   176.gcc:      srcalt 64bitgcc
   186.crafty:  -DLINUX_i386
   252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt fmax_errno
   253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
                -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
   254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
                -DSYS_HAS_SIGNAL_PROTO  -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
                -DSPEC_CPU2000_LP64
   255.vortex:  -DSPEC_CPU2000_LP64 srcalt closed_files

 Peak Tuning:
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  164.gzip:     basepeak = true
  175.vpr:     -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000
               -INLINE:aggressive=on -IPA:plimit=10000:callee_limit=5000
               +FDO
  176.gcc:     -O3 -ipa -OPT:goto=off +FDO
  181.mcf:     -O3 -ipa -IPA:field_reorder=on -m32 +FDO
  186.crafty:  -O3 -OPT:goto=off +FDO
  197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
  252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
               -TENV:X=4:frame_pointer=off -fno-exceptions
               -LNO:fu=10:full_unroll_outer=on -IPA:plimit=4000 +FDO
  253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
               -fno-math-errno -IPA:plimit=10000 +FDO
  254.gap:     -Ofast -WOPT:aggstr=off +FDO
  255.vortex:  -Ofast -OPT:goto=off -IPA:plimit=1800 -CG:p2align=on
               +FDO
  256.bzip2:    basepeak = true
  300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
               -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
               -WOPT:mem_opnds=on -m32 +FDO
The system under test can be built using a 13" x 16" SSI MEB case and an
Enermax EPS 12 Volt ATX-6ES 660 Watt power supply.
All memory slots were populated with Kingston KRX3200AK2 on all CPU(s).
Taskset utility used to bind CPU(s) to processes.
Memory timings were manually set in BIOS: CL=2.5, TRCD=3, TRAS=6, TRP=3
BIOS Rev E.1.02
```